

CREATEX

Wall covering adhesive

Art. 222 / 8 / 0423


VFL
Vismara Farbladen



Properties	CREATEX is a water-dilutable, low-odour, ready-to-use dispersion adhesive for interior wall coverings on walls and ceilings. CREATEX is easy and pleasant to apply, is economical in use and has a sufficiently long open time and is equipped with fungus-inhibiting additives.
Field of application	CREATEX is suitable for use on mineral substrates such as cement, lime or plastic plasters, masonry, exposed concrete, gypsum, etc. <ul style="list-style-type: none">– For textile wallpapers with or without paper backing– Textile coverings on foam or textile fabric– PVC-coated wallpaper with paper backing or polyester textile– Fibre Optics– Thin polystyrene
Pretreatment	The substrate must be clean, dry, dust-free, smooth and normally absorbent. Smooth out holes and unevenness with a suitable spatula. Fix untreated, absorbent, chalky or sandy substrates with a deep penetrating primer for the time being.
Processing	Apply the adhesive with a roller, brush or fine-toothed spatula. Apply the covering and remove any air bubbles in the mass using a plastic spatula. Remove excess glue with a sponge. Do not use below 10 °C.
Dilution	CREATEX is adjusted ready for use. If necessary, very little water can be added.
Extensiveness	150–250g per m ² and coat, depending on the substrate.
Application	Roller, brush or fine-toothed spatula. In order to achieve optimum results, it is very important to use the right tools – see KNUCHEL GUIDE on brush and roller qualities. You will find this guide both in the catalogue and on the homepage as an attachment to this product.
Cleaning	Clean tools with warm water immediately after use.
Delivery form	Packages of 20 and 10 kg.
Shelf life	CREATEX can be stored for up to 12 months in unopened original containers. Store in a cool but frost-free place. Diluted material reduces the shelf life, depending on the degree of dilution and water quality.
Viscosity	Paste-like, thixotropic
Density	1,05 ± 0,05 g/cm ³
Solid content	14 ± 1 %
Binder base	Acrylic resin dispersion
Colours	Transparent



Farben



Knuchel

High quality - Top finish

Registration	CPID 602132
Classification	For information on chemical properties and hazards as well as regulations regarding transport, processing, storage, disposal, etc., please refer to the safety data sheet.
Note	<p>This leaflet is only intended as a reference and non-binding advice. The processing must be adapted to the corresponding conditions. In special cases we recommend to contact our technical service. However, all data and information on the suitability and application of the delivered products do not exempt the processor from carrying out his own tests and trials. A claim for damages for omitted, incomplete or incorrect information is excluded. This applies in particular also if other products are used in the paint build-up system.</p> <p>Furthermore, we refer to our General Terms and Conditions (GTC) on our homepage.</p>