BLENDA®-XIT

Pigment primer WV-225

VFL Vismara Farbladen

Art. 225 / 2 / 0223



Properties BLENDA®-XIT is a water-dilutable, low-odor and strongly pigmented primer for

interior mineral surfaces. BLENDA®-XIT shows a good hardening effect and increases the covering and adhesive strength of subsequent coats. BLENDA®-XIT dries out without leaving a trace, is cloth-matt and remains breathable, low

tension and non-yellowing.

Field of application As a good covering primer on no longer highly absorbent surfaces such as

plaster, plasterboard, cement, concrete, sand-lime brick, cement-fibre board,

softwood fibre board, various building boards, etc.

Pretreatment The load-bearing substrate must be clean, dry and free from sintered layer,

grinding dust, oil, wax and other contaminants.

Processing Do not use below 8 °C.

System structure 1 x BLENDA®-XIT pigment primer WV-225

Drying ♦ Dry after 1–2 hours

♦ Overpaintable after 3–4 hours

(depending on the temperature, application quantity, air humidity and

absorbency of the substrate)

Dilution For rolling and brushing 0–5 %, for spraying dilute with up to 10–20 % water.

Extensiveness 5–7 m² per kg per application, depending on the quantity applied and the

condition of the substrate.

Application Brush, roller or spray gun.

In order to achieve optimum results, it is very important to use the right tools — see KNUCHEL GUIDE on brush and roller qualities. You will find this guide both in the actual rule and an the barrance are a see that the result is the contract to the result of the resu

in the catalogue and on the homepage as an attachment to this product.

Clean tools with warm water immediately after use. Dried-in residues can only

be removed with cleaning thinner or brush cleaner.

Delivery form Package of 20 kg.

Shelf life BLENDA®-XIT can be stored for at least 18 months in the well closed original

container. Store in a cool but frost-free place. Diluted material reduces the shelf

life, depending on the degree of dilution and water quality.

Viscosity Low viscosity / 950–1000 mPa.s

Density $1,46 \pm 0,05 \text{ g/cm}^3$

Solid content $54 \pm 1 \%$

Binder base Siloxane emulsion and modified acrylic resin dispersion

Pigment base Titanium dioxide




















auality - Top finis



Gloss level cloth mat

Colours White

Registration CPID 147215

Classification For information on chemical properties and hazards as well as regulations regarding transport, pro-

cessing, storage, disposal, etc., please refer to the safety data sheet.

Trademark BLENDA® is a registered trademark of Knuchel Farben AG in CH-Wiedlisbach.

NoteThis leaflet is only intended as a reference and non-binding advice. The processing must be adapted

to the corresponding conditions. In special cases we recommend to contact our technical service. However, all data and information on the suitability and application of the delivered products do not exempt the processor from carrying out his own tests and trials. A claim for damages for omitted, incomplete or incorrect information is excluded. This applies in particular also if other products are used

in the paint build-up system.

Furthermore, we refer to our General Terms and Conditions (GTC) on our homepage.