

XENOLIN

Impregnating solution

Art. 229 / 4 / 0323

VFL
Vismara Farbladen



Properties

XENOLIN is a water-based and ready-to-use impregnating solution with excellent water and dirt repellent properties. Due to these properties, the growth of microorganisms on substrates treated with XENOLIN is greatly reduced. At the same time, a very good soil-repellent effect is achieved against sunscreens, oils as well as foodstuffs such as mustard, ketchup, mayonnaise, fruit juices, red wine, etc. Excellent dirt-repellent results are also achieved with engine and waste oils. XENOLIN penetrates deep into the substrate and forms a breathable and dirt-repellent surface protection. XENOLIN is not film-forming and does not significantly alter the inherent color of the substrate.

Field of application

XENOLIN impregnating solution is suitable for all absorbent, mainly mineral surfaces such as concrete and cement slabs, various terrace slabs, paving stones, granite slabs, etc. Marble slabs and gravestones are also suitable for impregnation, but a preliminary test is recommended.

Important: An impregnated surface can no longer be painted over with a paint system afterwards. Treatment with a high-pressure cleaner or washing liquid is also unsuccessful. XENOLIN impregnating solution does not have food approval. An application such as on kitchen work surfaces where food comes into direct contact with the treated surface and is processed for consumption is therefore not suitable.

Processing

The substrate must be clean, dry and load-bearing. Contamination or an infestation with algae or lichens must first be cleaned thoroughly with a high-pressure cleaner, if possible without the addition of detergents. If the biological infestation cannot be removed, XENOZID biocide + algicide concentrate should be used.

After complete drying, the undiluted and ready-to-use XENOLIN solution is applied evenly and not too thickly with a roller, brush or paintbrush. To achieve optimum wetting, XENOLIN must not be used in direct sunlight. Depending on use, XENOLIN impregnation can be renewed after 2–5 years. Do not return remaining, unused goods to the original container to avoid contamination.

Drying

- ◆ Dry after 3–4 hours
- ◆ Walkable after approx. 24 hours
- ◆ Thoroughly dried and loadable after 3–4 days
(depending on the temperature, application quantity, air humidity and absorbency of the substrate)

Dilution

XENOLIN is adjusted ready for use.

Extensiveness

4–12 m² per litre per application, depending on the quantity applied and the condition of the substrate.


Application

Brush, brush or roller.

In order to achieve optimum results, it is very important to use the right tools – see KNUCHEL GUIDE on brush and roller qualities. You will find this guide both in the catalogue and on the homepage as an attachment to this product.



Farben



Knuchel

High quality - Top finish

Cleaning	Clean tools with warm water immediately after use. Contaminated tools with the dried product can no longer be cleaned with water and should be disposed of.
Renovation	XENOLIN cannot be overpainted. The renovation is only possible with the same product.
Delivery form	Packages of 5 litres as well as 1000ml and 500ml.
Shelf life	XENOLIN can be stored for at least 18 months in the well closed original container. Store in a cool but frost-free place.
Viscosity	Low viscosity / 10–14 seconds DIN 4mm
Density	1,00 ± 0,05 g/cm ³
Active substance	Contains: 3,7 % active ingredient (C6 fluorocarbon compound)
Registration	CPID 585680
Classification	For information on chemical properties and hazards as well as regulations regarding transport, processing, storage, disposal, etc., please refer to the safety data sheet.
Note	<p>This leaflet is only intended as a reference and non-binding advice. The processing must be adapted to the corresponding conditions. In special cases we recommend to contact our technical service. However, all data and information on the suitability and application of the delivered products do not exempt the processor from carrying out his own tests and trials. A claim for damages for omitted, incomplete or incorrect information is excluded. This applies in particular also if other products are used in the paint build-up system.</p> <p>Furthermore, we refer to our General Terms and Conditions (GTC) on our homepage.</p>