

ELOTOP

Rustic plaster type SP

Art. 558 / 2 / 0123

VFL
Vismara Farbladen



Properties

ELOTOP rustic plaster type SP is a water-dilutable, plastic-bonded and high-paste plastering compound with a fine grain size of 0,5–0,8mm for exterior and interior use. Thanks to the high viscosity setting and the good durability, it is possible to apply structurally beautiful wall coatings or smooth out minor unevenness in one operation. ELOTOP is breathable, elastic, shock and impact resistant and has excellent weather resistance.

Field of application

ELOTOP is suitable for use on mineral substrates such as cement, lime or plastic plasters, masonry, exposed concrete, gypsum, cement-fibre boards, wood and polystyrene.

- As decorative and rustic plastering compound
- As levelling ground
- As a mesh embedding material for a subsequent plaster application

Pretreatment

The substrate must be clean, dry and load-bearing. Old coatings must be cleaned (GEIGER SE-1 leachers / PUROL active cleaner concentrate) and tested for adhesion. Fix untreated, absorbent, chalky or sandy substrates with a deep penetrating primer for the time being.

Processing

Do not use below 8 °C or at high temperatures. Avoid direct sunlight, draughts and excessively warm surfaces (dehydration).

Stir ELOTOP well with a slowly rotating stirrer. Then apply ELOTOP evenly with stainless steel trowel and, depending on the application, smooth or texture (trowel, sponge, brush, etc.).

System structure

1 x BLENDAXIT®, DUROX deep penetrating primer or ELOTOP plaster primer concentrated W02
1–2 x ELOTOP rustic plaster type SP

Drying

- ◆ Firm to the touch after approx. 12 hours
- ◆ Reconditionable after 3–5 days
(depending on the temperature, application quantity, humidity and air circulation)

Dilution

ELOTOP is adjusted ready for use. For special applications it can be diluted with water.

Extensiveness

1–1,5 kg per m² and application, depending on the thickness of the coat.

Application

Steel trowel and plastic friction disc.

Cleaning

Clean tools with warm water immediately after use.

Delivery form


Packages of 25, 12 and 6 kg.

Shelf life

ELOTOP can be stored for at least 18 months in the well closed original container. Store in a cool but frost-free place. Diluted material reduces the shelf life, depending on the degree of dilution and water quality.



Farben



Knuchel

High quality - Top finish

Viscosity	High viscosity / 18000–2100 mPa.s
Solid content	85 ± 1 %
Binder base	Acrylic copolymer
Pigment base	Titanium dioxide
Fillers	Mineral fillers
Gloss level	Matt
Colours	Natural white Colour shade mixtures according to the colour charts Knuchel-Inspiration, RAL, Colortrend-E, NCS etc. or according to a template.
Registration	CPID 277334
Classification	For information on chemical properties and hazards as well as regulations regarding transport, processing, storage, disposal, etc., please refer to the safety data sheet.
Note	<p>This leaflet is only intended as a reference and non-binding advice. The processing must be adapted to the corresponding conditions. In special cases we recommend to contact our technical service. However, all data and information on the suitability and application of the delivered products do not exempt the processor from carrying out his own tests and trials. A claim for damages for omitted, incomplete or incorrect information is excluded. This applies in particular also if other products are used in the paint build-up system.</p> <p>Furthermore, we refer to our General Terms and Conditions (GTC) on our homepage.</p>