

DUOPRIM


Object dispersion

Art. 572 / 2 / 1222


VFL
Vismara Farbladen



| | |
|-----------------------------|--|
| Properties | DUOPRIM is an inexpensive and cloth-matt object dispersion paint for interior use. DUOPRIM is pleasantly easy to apply without leaving any build-up, has a low odour and hardly splashes when rolled. DUOPRIM coatings are characterized by good washability, covering and adhesive strength and alkali resistance. The coatings remain breathable and lightfast (no dark or light yellowing). |
| Field of application | As a wall and ceiling paint in industrial and residential construction, where a particularly high level of rub resistance and durability is not required. Suitable for all mineral surfaces such as cement, lime or plastic plasters, masonry, exposed concrete, gypsum, cement-fibre boards as well as wood, wallpaper, polystyrene, etc. |
| Pretreatment | The substrate must be clean, dry and load-bearing. Fix untreated, absorbent, chalky or sandy substrates with a deep penetrating primer for the time being. Wash off old lime and Blanc-Fix coats as thoroughly as possible and fix with a deep penetrating primer. Freshly applied plastic, silicone or mineral plasters must be thoroughly dry before painting over, otherwise stress cracks may occur. |
| Processing | Do not use below 8 °C. |
| System structure | <i>New construction on untreated substrates</i> BLENDA®-XIT deep penetrating primer WV-224 or DUROX deep penetrating primer 1–2 x DUOPRIM object dispersion <i>Renovation on intact old coats</i> 1–2 x DUOPRIM object dispersion |
| Drying | ◆ Dry after 1–3 hours ◆ Can be painted over after about 6 hours (depending on the temperature, application quantity and humidity) |
| Dilution | DUOPRIM has a ready-to-use consistency for roll and brush application. For spraying (depending on sprayer and nozzle size) dilute with 0–5 % water. |
| Extensiveness | 4–5 m ² per kg per application, depending on the quantity applied and the condition of the substrate. |
| Application | Spraying equipment (airless, aircoat, airmix, etc.) - Scooter and brush. In order to achieve optimum results, it is very important to use the right tools – see KNUCHEL GUIDE on brush and roller qualities. You will find this guide both in the catalogue and on the homepage as an attachment to this product. |
| Cleaning | Clean tools with warm water immediately after use. Dried-in residues can only be removed with cleaning thinner or brush cleaner. |
| Delivery form | Packages of 40 and 20 kg. |



Farben



Knuchel

High quality - Top finish

| | |
|-------------------------------|---|
| Shelf life | DUOPRIM can be stored for at least 18 months in the well closed original container. Store in a cool but frost-free place. Diluted material reduces the shelf life, depending on the degree of dilution and water quality. |
| Viscosity | DUOPRIM is set ready to roll and spread. Slightly thixotropic / 3200–3500 mPa.s |
| Density | 1,56 ± 0,05 g/cm ³ |
| Solid content | 56 ± 1 % |
| Binder base | Styrene acrylic copolymer dispersion |
| Pigment base | Titanium dioxide |
| Gloss level | Matt |
| Abrasion resistance | Wet abrasion class 3 according to DIN EN 13300. |
| Vapour diffusivity | sD value: 0,10 m / w1 value: 0,15 (kg/m ² -h ^{1/2}) |
| Colours | Natural white |
| Swiss Color Foundation | Environmental label: Class C (Minergie-Eco approved) |
| Registration | CPID 277703 |
| Classification | For information on chemical properties and hazards as well as regulations regarding transport, processing, storage, disposal, etc., please refer to the safety data sheet. |
| Note | <p>This leaflet is only intended as a reference and non-binding advice. The processing must be adapted to the corresponding conditions. In special cases we recommend to contact our technical service. However, all data and information on the suitability and application of the delivered products do not exempt the processor from carrying out his own tests and trials. A claim for damages for omitted, incomplete or incorrect information is excluded. This applies in particular also if other products are used in the paint build-up system.</p> <p>Furthermore, we refer to our General Terms and Conditions (GTC) on our homepage.</p> |