

DUROFIX

Acrylic interior dispersion ELF

Art. 66 / 2 / 1222

VFL
Vismara Farbladen



Properties

DUROFIX is a water-dilutable, emission- and odourless living room paint. The cloth-matt interior paint is completely solvent-free, resistant to washing and scrubbing, and convinces with its high covering power (in many cases one coat is sufficient) and its high coverage. DUROFIX is pleasantly easy to apply without leaving any build-up, has a low odour and hardly splashes when rolled. The coatings are characterised by low sensitivity to dirt, high adhesion and alkali resistance. The coatings remain breathable and lightfast (no dark or light yellowing).

Field of application

DUROFIX acrylic interior dispersion ELF is suitable for all mineral surfaces in new buildings as well as in the renovation sector, such as cement-, lime- or plastic plasters, masonry, exposed concrete, gypsum, cement fibre boards as well as wood, wallpaper, polystyrene, etc.

Pretreatment

The substrate must be clean, dry and load-bearing. Fix untreated, absorbent, chalky or sandy substrates with a deep penetrating primer for the time being. Wash off old lime and Blanc-Fix coats as thoroughly as possible and fix with a deep penetrating primer.

Processing

Do not use below 8 °C.

System structure

New construction on untreated substrates

BLENDA®-XIT deep penetrating primer WV-224 or DUROX deep penetrating primer

1–2 x DUROFIX acrylic interior dispersion ELF

Renovation on intact old coats

1–2 x DUROFIX acrylic interior dispersion ELF

Drying

- ◆ Dry after 1–3 hours
- ◆ Can be painted over after about 6 hours
(depending on the temperature, application quantity and soil moisture)

Dilution

Water. Dilute with 5–10 % for rolling and brushing. Dilute with 10–15 % for spraying and for painting over plasters.

Extensiveness

4–5 m² per kg per application, depending on the quantity applied and the condition of the substrate.

Application

Brush, roller or spray gun.


In order to achieve optimum results, it is very important to use the right tools – see KNUCHEL GUIDE on brush and roller qualities. You will find this guide both in the catalogue and on the homepage as an attachment to this product.

Cleaning

Clean tools with warm water immediately after use. Dried-in residues can only be removed with cleaning thinner or brush cleaner.

Delivery form

Packages of 20, 10 and 5 kg.



Shelf life	DUROFIX can be stored for at least 18 months in the well closed original container. Store in a cool but frost-free place. Diluted material reduces the shelf life, depending on the degree of dilution and water quality.
Viscosity	Paste-like, thixotropic / 4800–5200 mPa.s
Density	1,70 ± 0,05 g/cm ³
Solid content	69 ± 1 %
Binder base	Modified vinyl acetate-ethylene copolymer dispersion
Pigment base	Titanium dioxide, inorganic and organic coloured pigments.
Gloss level	Matt
Colours	White, RAL 9010 and NCS S 0500-N.
Swiss Color Foundation	Environmental label: Class B (Minergie-Eco and ecobau BKP/Devis approved, 1st priority)
Classification	For information on chemical properties and hazards as well as regulations regarding transport, processing, storage, disposal, etc., please refer to the safety data sheet.
Note	<p>This leaflet is only intended as a reference and non-binding advice. The processing must be adapted to the corresponding conditions. In special cases we recommend to contact our technical service. However, all data and information on the suitability and application of the delivered products do not exempt the processor from carrying out his own tests and trials. A claim for damages for omitted, incomplete or incorrect information is excluded. This applies in particular also if other products are used in the paint build-up system.</p> <p>Furthermore, we refer to our General Terms and Conditions (GTC) on our homepage.</p>