HAMMER

Hammer finish spray

Art. 744 / 9 / 0423





Properties Gives the surface a metallic hammered structure with a high decorative and

sales-promoting effect. The paints are extremely resistant and due to the good filling power, excellent results are achieved even with smaller unevenness of

the substrate.

Pretreatment Remove grease, dirt and rust. If necessary, apply an anti-rust primer (SUPER-

PRIMER primer spray, ACRYL-PRIMER universal primer spray). Carefully cover

areas not to be sprayed.

Processing Avoid sun and wind. Shake the can before use until the balls move audibly for

about 20 seconds. Shake well even when working in between. Spray distance 25–30cm. Spray thin layers in the cloister. Wait a few minutes after each shift,

but no longer than 30 minutes.

Drying ◆ Dust dry after 20–30 minutes

♦ Firm to the touch after approx. 1 hour

◆ Fully dried after about 6 hours

Extensiveness 0,5–1,5 m², depending on the colour shade, the quantity applied and the con-

dition of the substrate.

Cleaning With self-cleaning special valve. It is no longer necessary to reverse the can

after use to clean the valve by means of gas leakage.

Delivery form Aerosol cans of 400ml.

Shelf life HAMMER can be stored for at least 24 months in the well closed original con-

tainer.

Gloss level Silky Gloss

Colours No. 11 blue, No. 12 green, No. 13 silver, No. 17 anthracite

Registration CPID 627803

Classification For information on chemical properties and hazards as well as regulations

regarding transport, processing, storage, disposal, etc., please refer to the safety

data sheet.

Note This leaflet is only intended as a reference and non-binding advice. The pro-

cessing must be adapted to the corresponding conditions. In special cases we recommend to contact our technical service. However, all data and information on the suitability and application of the delivered products do not exempt the processor from carrying out his own tests and trials. A claim for damages for omitted, incomplete or incorrect information is excluded. This applies in partic-

ular also if other products are used in the paint build-up system.

Furthermore, we refer to our General Terms and Conditions (GTC) on our

homepage.

















Knuche