METALLIC

Anodized bronze spray

Art. 763 / 9 / 0423





Properties METALLIC is a high quality product for the color-accurate painting and varnish

repair of surface scratches and other damage to anodized surfaces such as doors, windows, shower enclosures, etc. as well as for color matching of all

kinds of accessories.

Field of application
It is suitable for high-quality paintwork on machine and vehicle parts and as a

universal decorative paint on metal and wood.

Pretreatment Remove grease, dirt and rust. If necessary, apply an anti-rust primer (SUPER-

PRIMER primer spray, ACRYL-PRIMER universal primer spray). Carefully cover

areas not to be sprayed.

ProcessingAvoid sun and wind. Shake the can before use until the balls move audibly for

about 20 seconds. Shake well even when working in between. Spray distance 25–30cm. Spray thin layers in the cloister. Wait a few minutes after each shift,

but no longer than 30 minutes.

Drying ◆ Dust dry after 10–20 minutes

• Firm to the touch after approx. 30 minutes

◆ Fully dried after about 2 hours

Extensiveness 1–2 m², depending on the colour shade, the quantity applied and the condition

of the substrate.

Cleaning With self-cleaning special valve. It is no longer necessary to reverse the can

after use to clean the valve by means of gas leakage.

Delivery form Aerosol cans of 400ml.

Shelf life METALLIC can be stored for at least 24 months in the well closed original

container.

Gloss level Gloss

Colours No. 56 dark bronze, No. 57 middle bronze, No. 58 bronze.

Registration CPID 104148

Classification For information on chemical properties and hazards as well as regulations

regarding transport, processing, storage, disposal, etc., please refer to the safety

data sheet.

Note This leaflet is only intended as a reference and non-binding advice. The pro-

cessing must be adapted to the corresponding conditions. In special cases we recommend to contact our technical service. However, all data and information on the suitability and application of the delivered products do not exempt the processor from carrying out his own tests and trials. A claim for damages for

omitted, incomplete or incorrect information is excluded. This applies in particular also if other products are used in the paint build-up system.





















mality - Ton fini



Furthermore, we refer to our General Terms and Conditions (GTC) on our homepage.