

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

VFL
Vismara Farbladen

Article No.: 1409
Print date: 29.01.2021
Version: 6

ECLON PUR
Revision date: 30.07.2020
Issue date: 30.07.2020

EN
Page 1 / 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. **product identifiers**

Article No. (manufacturer/supplier) 1409
Trade name/designation ECLON PUR
2K-phosphate primer

1.2. **Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses:

Coating material to protect surfaces

1.3. **Details of the supplier of the safety data sheet**

supplier (manufacturer/importer/downstream user/distributor)
Vismara Unternehmungen CH-5000 Aarau www.farbladen.ch

Department responsible for information:

Labor
E-mail

1.4. **Emergency telephone number**

Emergency telephone number +41 32 622 41 41
Toxikologisches Zentrum +41 44 251 51 51

SECTION 2: Hazards identification

2.1. **Classification of the substance or mixture** *

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

2.2. **Label elements** *

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Warning

Hazard statements

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapour.
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.
P403 + P235 Store in a well-ventilated place. Keep cool.

Hazard components for labelling

Xylene

Supplemental hazard information

not applicable

2.3. **Other hazards**

No information available.

SECTION 3: Composition / information on ingredients

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 1409
Print date: 29.01.2021
Version: 6

ECLON PUR
Revision date: 30.07.2020
Issue date: 30.07.2020

EN
Page 2 / 12

3.2. Mixtures

Description Acryl-Polyurethan-Kombination

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No.	REACH No.	weight-%
CAS No.	Designation	
Index No.	classification // Remark	
215-535-7	01-2119488216-32	
1330-20-7	Xylene	12.5 - 20
601-022-00-9	Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / STOT SE 3 H335 / STOT RE 2 H373 / Asp. Tox. 1 H304 / Flam. Liq. 3 H226	
202-849-4	01-2119489370-35	
100-41-4	ethylbenzene	2.5 - 5
601-023-00-4	Flam. Liq. 2 H225 / Acute Tox. 4 H332 / STOT RE 2 H373 / Asp. Tox. 1 H304	
204-658-1	01-2119485493-29	
123-86-4	n-butyl acetate	1 - 2.5
607-025-00-1	Flam. Liq. 3 H226 / STOT SE 3 H336	
203-603-9	01-2119475791-29	
108-65-6	2-methoxy-1-methylethyl acetate	1 - 2.5
607-195-00-7	Flam. Liq. 3 H226 Substance with a common (EC) occupational exposure limit value.	

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 1409
Print date: 29.01.2021
Version: 6

ECLON PUR
Revision date: 30.07.2020
Issue date: 30.07.2020

EN
Page 3 / 12

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

WEL, TWA: 220 mg/m³; 50 ppm

WEL, STEL: 441 mg/m³; 100 ppm

Remark: (may be absorbed through the skin)

BMGV, TWA: 650 mmol/mol creatinine

Remark: methyl hippuric acid; urine; end of exposure or end of shift

*

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 1409
Print date: 29.01.2021
Version: 6

ECLON PUR
Revision date: 30.07.2020
Issue date: 30.07.2020

EN
Page 4 / 12

ethylbenzene

Index No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

WEL, TWA: 441 mg/m³; 100 ppm

WEL, STEL: 552 mg/m³; 125 ppm

Remark: (may be absorbed through the skin)

n-butyl acetate

Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

MEL/OES, TWA: 724 mg/m³; 150 ppm

MEL/OES, STEL: 966 mg/m³; 200 ppm

2-methoxy-1-methylethyl acetate

Index No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

WEL, TWA: 274 mg/m³; 50 ppm

WEL, STEL: 548 mg/m³; 100 ppm

Remark: (may be absorbed through the skin)

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

DNEL long-term dermal (systemic), Workers: 212 mg/kg bw/day

DNEL acute inhalative (local), Workers: 442 mg/m³

DNEL acute inhalative (systemic), Workers:

DNEL long-term inhalative (local), Workers: 221 mg/m³

DNEL long-term inhalative (systemic), Workers: 221 mg/m³

DNEL long-term oral (repeated), Consumer: 12,5 mg/kg bw/day

DNEL long-term dermal (systemic), Consumer: 125 mg/kg bw/day

DNEL acute inhalative (local), Consumer: 260 mg/m³

DNEL acute inhalative (systemic), Consumer: 260 mg/m³

DNEL long-term inhalative (local), Consumer: 65,3 mg/m³

DNEL long-term inhalative (systemic), Consumer: 65,3 mg/m³

ethylbenzene

Index No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

DNEL long-term dermal (systemic), Workers: 180 mg/kg bw/day

DNEL long-term inhalative (systemic), Workers: 77 mg/m³

DNEL long-term oral (repeated), Consumer: 1,6 mg/kg bw/day

DNEL long-term inhalative (systemic), Consumer: 15 mg/m³

n-butyl acetate

Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

DNEL long-term inhalative (systemic), Workers: 480 mg/m³

DNEL long-term inhalative (systemic), Consumer: 102,34 mg/m³

2-methoxy-1-methylethyl acetate

Index No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

DNEL long-term oral (repeated), Workers: 1,67 mg/kg

DNEL long-term dermal (systemic), Workers: 54,8 mg/kg

DNEL long-term inhalative (systemic), Workers: 33 mg/m³

PNEC:

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

PNEC aquatic, freshwater: 0,327 mg/L

PNEC aquatic, marine water: 0,327 mg/L

PNEC sediment, freshwater: 12,46 mg/kg

PNEC sediment, marine water: 12,46 mg/kg

PNEC, soil: 2,31 mg/kg

PNEC sewage treatment plant (STP): 6,58 mg/L

ethylbenzene

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 1409
Print date: 29.01.2021
Version: 6

ECLON PUR
Revision date: 30.07.2020
Issue date: 30.07.2020

EN
Page 5 / 12

Index No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

PNEC aquatic, freshwater: 0,1 mg/L
PNEC aquatic, marine water: 0,01 mg/L
PNEC sediment, freshwater: 13,7 mg/kg
PNEC sediment, marine water: 1,37 mg/kg
PNEC, soil: 2,68 mg/kg
PNEC sewage treatment plant (STP):

n-butyl acetate

Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

PNEC aquatic, freshwater: 0,18 mg/L
PNEC aquatic, marine water: 0,018 mg/L
PNEC aquatic, intermittent release: 0,36 mg/L
PNEC sediment, freshwater: 0,981 mg/kg Sediment dry weight
PNEC sediment, marine water: 0,0981 mg/kg Sediment dry weight
PNEC, soil: 0,0903 mg/kg Sediment dry weight
PNEC sewage treatment plant (STP): 35,6 mg/L

2-methoxy-1-methylethyl acetate

Index No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

PNEC aquatic, freshwater: 0,635 mg/cm³
PNEC aquatic, marine water: 0,0635 mg/cm³
PNEC aquatic, intermittent release: 6,35 mg/cm³
PNEC sediment, freshwater: 3,29 mg/cm³
PNEC sediment, marine water: 0,329 mg/cm³
PNEC, soil: 0,29 mg/m³
PNEC sewage treatment plant (STP): 100 mg/cm³

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)
Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state:

Liquid

Colour:

refer to label

Odour:

characteristic

Odour threshold:

not applicable

*

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 1409
Print date: 29.01.2021
Version: 6

ECLON PUR
Revision date: 30.07.2020
Issue date: 30.07.2020

EN
Page 6 / 12

pH at 20 °C:	not applicable
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	139 °C Source: Xylene
Flash point:	45 °C Method: DIN 53213
Evaporation rate:	not applicable
flammability	
Burning time:	not applicable
Upper/lower flammability or explosive limits:	
Lower explosion limit:	0.93 Vol-%
Upper explosion limit:	8 Vol-% Source: Xylene
Vapour pressure at 20 °C:	1.01 mbar
Vapour density:	not applicable
Relative density:	
Density at 20 °C:	1.67 g/cm³
Solubility(ies):	
Water solubility at 20 °C:	insoluble
Partition coefficient: n-octanol/water:	see section 12
Auto-ignition temperature:	333 °C Source: 2-methoxy-1-methylethyl acetate
Decomposition temperature:	not applicable
Viscosity at 20 °C:	100 s 6 mm Method: DIN 53211
Explosive properties:	not applicable
Oxidising properties:	not applicable
9.2. Other information	*
Solid content:	79 weight-%
solvent content:	
Organic solvents:	21 weight-%
Water:	0 weight-%
Solvent separation test:	< 3 weight-% (ADR/RID)

SECTION 10: Stability and reactivity

- 10.1. **Reactivity**
No information available.
- 10.2. **Chemical stability**
Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.
- 10.3. **Possibility of hazardous reactions**
Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.
- 10.4. **Conditions to avoid** *
- Hazardous decomposition byproducts may form with exposure to high temperatures.
- 10.5. **Incompatible materials**
not applicable
- 10.6. **Hazardous decomposition products**
Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

- 11.1. **Information on toxicological effects** *

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 1409
Print date: 29.01.2021
Version: 6

ECLON PUR
Revision date: 30.07.2020
Issue date: 30.07.2020

EN
Page 7 / 12

Acute toxicity

Xylene

oral, LD50, Rat: 4300 mg/kg
dermal, LD50, Rabbit: 2000 mg/kg
oral, LD50, Rat, male: 5,523 mg/kg
Method: EU Test B.1
Algae toxicity, EC50, Pseudokirchneriella subcapitata: 2,2 mg/L (73 h)
Method: OECD 201
inhalative (vapours), LC50, Rat, male: 6700 ppm (4 h)

ethylbenzene

oral, LD50, Rat: 3,5 mg/kg
dermal, LD50, Rabbit: 15,4 mg/kg

n-butyl acetate

oral, LD50, Rat: 10760 mg/kg
Method: OECD 423
dermal, LD50, Rabbit: 14112 mg/kg
Method: OECD 402
inhalative (dust and mist), LC50, Rat: 23,4 mg/L (4 h)
Method: OECD 403

2-methoxy-1-methylethyl acetate

dermal, LD50, Rabbit: > 2000 mg/kg

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye irritation.

ethylbenzene

Skin, Rabbit (24 h)
Causes mild skin irritation.
eyes, Rabbit
Causes slight eye irritation

n-butyl acetate

Skin, Rabbit (4 h)
Method: OECD 404
No skin irritation
eyes
Method: OECD 405
No eye irritation

2-methoxy-1-methylethyl acetate

Skin (4 h)
Method: OECD 404
Not to be classified as skin etching/irritant.
eyes
Not to be classified as severe eye damage or eye irritation.

Respiratory or skin sensitisation

n-butyl acetate

Skin, Guinea pig: ; Evaluation not sensitising.
Method: OECD 406
Mouse mouse ear swelling test (MEST)

2-methoxy-1-methylethyl acetate

Skin: ; Evaluation not sensitising.
Method: OECD 406
Respiratory system:
No data available

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

ethylbenzene

Germ cell mutagenicity; Evaluation negative
Hamster; Mouse; ovaries

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 1409
Print date: 29.01.2021
Version: 6

ECLON PUR
Revision date: 30.07.2020
Issue date: 30.07.2020

EN
Page 8 / 12

Carcinogenicity; Evaluation Carc. Cat. 2
Method: Group II B (IARC): Possible carcinogenic to humans (ethylbenzene)
human

n-butyl acetate
Germ cell mutagenicity; Evaluation Ames test negative.

2-methoxy-1-methylethyl acetate

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Lactation

No data available

STOT-single exposure; STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Xylene

Specific target organ toxicity (repeated exposure)

Liver and kidney damage; central nervous system

Causes damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).

Liver and kidney damage; central nervous system; hearing organs

ethylbenzene

Repeated dose toxicity, Rat: 75 mg/kg

Method OECD 407

RTECS-no.;; DA0700000

depression of central nervous system

movement disorders; headache; Vomiting

n-butyl acetate

Specific target organ toxicity (single exposure)

central nervous system; May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure)

human; Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).; Steam in high concentration leads to unconsciousness.

2-methoxy-1-methylethyl acetate

Specific target organ toxicity (single exposure)

No data available

Specific target organ toxicity (repeated exposure)

No data available

Aspiration hazard

n-butyl acetate

Aspiration hazard; Evaluation No classification for aspiration toxicity

2-methoxy-1-methylethyl acetate

Aspiration hazard

No data available

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 1409
Print date: 29.01.2021
Version: 6

ECLON PUR
Revision date: 30.07.2020
Issue date: 30.07.2020

EN
Page 9 / 12

Do not allow to enter into surface water or drains.

12.1. Toxicity

Xylene

Fish toxicity, LC50, fish: 2,6 mg/L (96 h)
Method: OECD 203
Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 4,6 mg/L (72 h)
Method: OECD 201
Algae toxicity, LC50, Pseudokirchneriella subcapitata: 4,6 mg/L (72 h)
Method: OECD 201
Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout) (96 h)
Method: OECD 203
Daphnia toxicity, IC50, Daphnia magna: 1 mg/L (24 h)
Method: OECD 202
Algae toxicity, LC50, Selenastrum capricornutum: 2,2 mg/L (73 h)
Method: OECD 201
Bacteria toxicity, NOEC, Activated sludge: 16 mg/L (28 d)
Method: OECD 301 F

ethylbenzene

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 4,2 mg/L (96 h)
Daphnia toxicity, EC50, Daphnia magna 1,8 - 2,4 mg/L (48 h)
Algae toxicity, EC50, Skeletonema costatum: 4,9 mg/L (72 h)
Algae toxicity, EC50, Pseudokirchneriella subcapitata: 7,2 mg/L (48 h)
Shellfish Toxicity, LC50, Mysidopsis bahia: > 5,2 mg/L (48 h)
Toxicity of Microorganisms, EC50, microorganisms: 96 mg/L (24 h)

n-butyl acetate

Fish toxicity, LC50: 18 mg/L (96 h)
Method: OECD 203
Daphnia toxicity, EC50, Daphnia magna (Big water flea): 44 mg/L (48 h)
Algae toxicity, EC50, Desmodesmus subspicatus: 647,7 mg/L (72 h)
(Growth inhibition)
Algae toxicity, NOEC, Desmodesmus subspicatus: 200 mg/L
(Growth inhibition)
Bacteria toxicity, IC50, Tetrahymena: 356 mg/L (40 h)

Long-term Ecotoxicity

Xylene

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 4,36 mg/L (73 h)
Method: OECD 201
Fish toxicity, NOEC, fish: > 1,3 mg/L (56 d)
Daphnia toxicity, EL50, Daphnia magna: 2,9 mg/L (21 d)
Method: OECD 211
Daphnia toxicity, NOEC, Daphnia pulex: 1,17 mg/L (7 d)
Method: US EPA 600/4-91-003
Daphnia toxicity, LOEC:, Daphnia magna (Big water flea): 3,16 mg/L (21 d)
Method: OECD 211
Algae toxicity, growth test (Eb-Cx) 10%“, Pseudokirchneriella subcapitata: 0,72 mg/L (73 h)
Method: OECD 201
Daphnia toxicity, growth test (Eb-Cx) 10%“, Daphnia magna: 1,91 mg/L (21 d)
Method: OECD 211

ethylbenzene

Daphnia toxicity, NOEC, Ceriodaphnia dubia (Wasserfloh): 0,96 mg/L (7 d)
Algae toxicity, NOEC, Pseudokirchneriella subcapitata: 3,4 mg/L (96 h)
Daphnia toxicity, LC50, Ceriodaphnia dubia (Wasserfloh): 3,6 mg/L (7 d)
Bacteria toxicity, EC50, Nitrosomonas sp: 96 mg/L (24 h)
Daphnia toxicity, LOEC:, Ceriodaphnia dubia (Wasserfloh): 1,7 mg/L (7 d)

12.2. Persistence and degradability

Xylene

Persistence and degradability:
Method: Rapid photochemical oxidation in air
Biodegradation: 98 percent (28 d)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 1409
Print date: 29.01.2021
Version: 6

ECLON PUR
Revision date: 30.07.2020
Issue date: 30.07.2020

EN
Page 10 / 12

Readily biodegradable (according to OECD criteria)

ethylbenzene

Biodegradation, aerobic: 70 - 80 percent (28 d); Evaluation Readily biodegradable (according to OECD criteria).

n-butyl acetate

Persistence and degradability: Evaluation No data available

Biodegradation: 83 percent (28 d); Evaluation Readily biodegradable (according to OECD criteria).

Method: OECD 301D

aerobic.

2-methoxy-1-methylethyl acetate

Biodegradation: Evaluation Readily biodegradable (according to OECD criteria).

Persistence and degradability:

No data available

12.3. Bioaccumulative potential

Xylene

Distribution coefficient n-octanol/water (log KOW): 3,49

ethylbenzene

Distribution coefficient n-octanol/water (log KOW): 3,6

n-butyl acetate

Distribution coefficient n-octanol/water (log KOW):

No data available

2-methoxy-1-methylethyl acetate

Distribution coefficient n-octanol/water (log KOW): 1,2

12.4. Mobility in soil

Xylene

soil: Evaluation Absorbs slowly into the soil

Water: Evaluation Floats on the water

n-butyl acetate

:

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

UN 1263

14.2. UN proper shipping name

Land transport (ADR/RID):

Paint

Sea transport (IMDG):

PAINT

Air transport (ICAO-TI / IATA-DGR):

Paint

14.3. Transport hazard class(es)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 1409
 Print date: 29.01.2021
 Version: 6

ECLON PUR
 Revision date: 30.07.2020
 Issue date: 30.07.2020

EN
 Page 11 / 12

Land transport (ADR/RID):	KEINE GÜTER DER KLASSE 3 bei Gebinden > 450 l Klasse 3
Sea transport (IMDG) for packages < 30 litres:	3 Transport in accordance with 2.3.2.5 of the IMDG Code.
Air transport (ICAO-TI / IATA-DGR)	3
14.4. Packing group	III
14.5. Environmental hazards	
Land transport (ADR/RID)	not applicable
Marine pollutant	not applicable
14.6. Special precautions for user	
Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage. Advices on safe handling: see parts 6 - 8	
Further information	
Land transport (ADR/RID)	
tunnel restriction code	D/E
Sea transport (IMDG)	
EmS-No.	F-E, S-E
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
not applicable	

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**
- EU legislation**
- Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**
 VOC-value (in g/L): 355
- National regulations**
- Restrictions of occupation**
 Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
 Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
215-535-7 1330-20-7	Xylene	01-2119488216-32
202-849-4 100-41-4	ethylbenzene	01-2119489370-35
204-658-1 123-86-4	n-butyl acetate	01-2119485493-29
203-603-9 108-65-6	2-methoxy-1-methylethyl acetate	01-2119475791-29

SECTION 16: Other information

Full text of classification in section 3

Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 1409
Print date: 29.01.2021
Version: 6

ECLON PUR
Revision date: 30.07.2020
Issue date: 30.07.2020

EN
Page 12 / 12

Asp. Tox. 1 / H304 Aspiration hazard
Flam. Liq. 3 / H226 Flammable liquids
Flam. Liq. 2 / H225 Flammable liquids
STOT SE 3 / H336 STOT-single exposure

is conclusively proven that no other routes of exposure cause the hazard).
May be fatal if swallowed and enters airways.
Flammable liquid and vapour.
Highly flammable liquid and vapour.
May cause drowsiness or dizziness.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 Flammable liquids On basis of test data.
Skin Irrit. 2 Skin corrosion/irritation Calculation method.
Eye Irrit. 2 Serious eye damage/eye irritation Calculation method.
STOT RE 2 STOT-repeated exposure Calculation method.

Abbreviations and acronyms

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL Occupational Exposure Limit Value
BLV Biological Limit Value
CAS Chemical Abstracts Service
CLP Classification, Labelling and Packaging
CMR Carcinogenic, Mutagenic and Reprotoxic
DIN German Institute for Standardization / German industrial standard
DNEL Derived No-Effect Level
EAKV European Waste Catalogue Directive
EC Effective Concentration
EC European Community
EN European Standard
IATA-DGR International Air Transport Association – Dangerous Goods Regulations
IBC Code International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code International Maritime Code for Dangerous Goods
ISO International Organization for Standardization
LC Lethal Concentration
LD Lethal Dose
MARPOL Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD Organisation for Economic Cooperation and Development
PBT persistent, bioaccumulative, toxic
PNEC Predicted No Effect Concentration
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals
RID Regulations concerning the International Carriage of Dangerous Goods by Rail
UN United Nations
VOC Volatile Organic Compounds
vPvB very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version