

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

VFL
Vismara Farbladen

Article No.: 170
Print date: 26.12.2022
Version: 3.0

BRILAC Glanzzusatz
Revision date: 10.12.2022
Issue date: 10.12.2022

EN
Page 1 / 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. **product identifiers**

Article No. (manufacturer/supplier) 170
Trade name/designation BRILAC Glanzzusatz

1.2. **Relevant identified uses of the substance or mixture and uses advised against**

1.3. **Details of the supplier of the safety data sheet**

supplier (manufacturer/importer/downstream user/distributor)
Vismara Unternehmungen CH-5000 Aarau www.farbladen.ch

Department responsible for information:

laboratory Manager
E-mail (competent person) info@knuchel.ch

1.4. **Emergency telephone number**

Emergency telephone number 145 (+41 (0)44 251 51 51)

SECTION 2: Hazards identification

2.1. **Classification of the substance or mixture**

*

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.

2.2. **Label elements**

*

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Warning

Hazard statements

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing vapours.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves and eye/face protection.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Keep locked up.
P501 Dispose of contents/container to industrial incineration plant.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 170
 Print date: 26.12.2022
 Version: 3.0

BRILAC Glanzzusatz
 Revision date: 10.12.2022
 Issue date: 10.12.2022

EN
 Page 2 / 13

Hazard components for labelling

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Supplemental hazard information

EUH208 Contains reaction mass of
 α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and
 α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)pro
 Fatty acid C6-C19, cobalt salt. May produce an allergic reaction.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description solvent-based alkyd resin, containing the following hazardous substances:

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification // Remark	weight-%
919-446-0	01-2119458049-33 Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) STOT SE 3 H336 / Asp. Tox. 1 H304 / Aquatic Chronic 2 H411 / Flam. Liq. 3 H226	15 - 25
215-535-7 1330-20-7 601-022-00-9	01-2119488216-32 Xylene Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / STOT SE 3 H335 / STOT RE 2 H373 / Asp. Tox. 1 H304 / Flam. Liq. 3 H226	5 - 10
919-857-5	01-2119463258-33 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics STOT SE 3 H336 / Asp. Tox. 1 H304 / Flam. Liq. 3 H226	1 - 5
202-849-4 100-41-4 601-023-00-4	01-2119489370-35 ethylbenzene Flam. Liq. 2 H225 / Acute Tox. 4 H332 / STOT RE 2 H373 / Asp. Tox. 1 H304	1 - 5
400-830-7 607-176-00-3	01-0000015075-76 reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxy poly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2- H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) Skin Sens. 1 H317 / Aquatic Chronic 2 H411	0.5 - 1
245-018-1 22464-99-9	Fatty acid C6-C19, zirconium Repr. 2 H361	0.1 - 0.5
270-066-5 68409-81-4	Fatty acid C6-C19, cobalt salt Acute Tox. 4 H302 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Repr. 1B H360 / Aquatic Chronic 2 H411	0.1 - 0.5
271-378-4 68551-44-0	01-2119979093-30 FATTY C6-C19, ZINC SOAP Eye Irrit. 2 H319 / Repr. 2 H361 / Asp. Tox. 1 H304 / Aquatic Chronic 3 H412	0.1 - 0.5

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 170
Print date: 26.12.2022
Version: 3.0

BRILAC Glanzzusatz
Revision date: 10.12.2022
Issue date: 10.12.2022

EN
Page 3 / 13

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 170
Print date: 26.12.2022
Version: 3.0

BRILAC Glanzzusatz
Revision date: 10.12.2022
Issue date: 10.12.2022

EN
Page 4 / 13

protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSIVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

WEL, TWA: 220 mg/m³; 50 ppm

WEL, STEL: 441 mg/m³; 100 ppm

Remark: (may be absorbed through the skin)

BMGV, TWA: 650 mmol/mol creatinine

Remark: methyl hippuric acid; urine; end of exposure or end of shift

ethylbenzene

Index No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

WEL, TWA: 441 mg/m³; 100 ppm

WEL, STEL: 552 mg/m³; 125 ppm

Remark: (may be absorbed through the skin)

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

DNEL long-term dermal (systemic), Workers: 212 mg/kg bw/day

DNEL acute inhalative (local), Workers: 442 mg/m³

DNEL acute inhalative (systemic), Workers: 442 mg/m³

DNEL long-term inhalative (local), Workers:

DNEL long-term inhalative (systemic), Workers: 221 mg/m³

DNEL long-term oral (repeated), Consumer: 12,5 mg/kg bw/day

DNEL long-term dermal (systemic), Consumer: 125 mg/kg bw/day

DNEL acute inhalative (local), Consumer: 260 mg/m³

DNEL acute inhalative (systemic), Consumer: 260 mg/m³

DNEL long-term inhalative (local), Consumer: 65,3 mg/m³

DNEL long-term inhalative (systemic), Consumer: 65,3 mg/m³

ethylbenzene

Index No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

DNEL long-term dermal (systemic), Workers: 180 mg/kg bw/day

DNEL long-term inhalative (systemic), Workers: 77 mg/m³

DNEL long-term oral (repeated), Consumer: 1,6 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 170
Print date: 26.12.2022
Version: 3.0

BRILAC Glanzzusatz
Revision date: 10.12.2022
Issue date: 10.12.2022

EN
Page 5 / 13

DNEL long-term inhalative (systemic), Consumer: 15 mg/m³
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
EC No. 919-446-0

DNEL long-term dermal (local), Workers: 44 mg/kg
DNEL long-term dermal (systemic), Workers: 44 mg/kg
DNEL acute inhalative (local), Workers: 570 mg/m³
DNEL acute inhalative (systemic), Workers: 570 mg/m³
DNEL long-term inhalative (local), Workers: 330 mg/m³
DNEL long-term inhalative (systemic), Workers: 330 mg/m³
DNEL long-term oral (repeated), Consumer: 26 mg/kg
DNEL long-term dermal (local), Consumer: 26 mg/kg
DNEL long-term dermal (systemic), Consumer: 26 mg/kg
DNEL acute inhalative (local), Consumer: 570 mg/m³
DNEL long-term inhalative (local), Consumer: 71 mg/m³
DNEL long-term inhalative (systemic), Consumer: 71 mg/m³

PNEC:

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

PNEC aquatic, freshwater: 0,327 mg/L
PNEC aquatic, marine water: 0,327 mg/L
PNEC sediment, freshwater: 12,46 mg/kg
PNEC sediment, marine water: 12,46 mg/kg
PNEC sewage treatment plant (STP): 6,58 mg/L
soil: 2,31 mg/kg

ethylbenzene

Index No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

PNEC aquatic, freshwater: 0,1 mg/L
PNEC aquatic, marine water: 0,01 mg/L
PNEC sediment, freshwater: 13,7 mg/kg
PNEC sediment, marine water: 1,37 mg/kg
PNEC, soil: 2,68 mg/kg
PNEC sewage treatment plant (STP): 9,6 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

*

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 170
Print date: 26.12.2022
Version: 3.0

BRILAC Glanzzusatz
Revision date: 10.12.2022
Issue date: 10.12.2022

EN
Page 6 / 13

Colour:	refer to label
Odour:	characteristic
Odour threshold:	not applicable
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	139 °C Source: Xylene
Flammability:	Flammable liquid and vapour.
Lower and upper explosion limit:	
Lower explosion limit:	0.74 Vol-%
Upper explosion limit:	8 Vol-% Source: Xylene
Flash point:	25 °C Method: DIN 53213
Auto-ignition temperature:	240 °C Source: Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics
Decomposition temperature:	not applicable
pH at 20 °C:	not applicable
Cinematic viscosity (40°C):	729.62 mm²/s
Viscosity at 20 °C:	800±200 mPas
Solubility(ies):	
Water solubility at 20 °C:	insoluble
Partition coefficient: n-octanol/water:	see section 12
Vapour pressure at 20 °C:	8 mbar Source: Xylene
Density and/or relative density:	
Density at 20 °C:	0.96 g/cm³
Relative vapour density:	not applicable
particle characteristics:	not applicable
9.2. Other information	*
Solid content:	57 weight-%
solvent content:	
Organic solvents:	43 weight-%
Water:	0 weight-%
Solvent separation test:	< 3 weight-% (ADR/RID)

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 170
Print date: 26.12.2022
Version: 3.0

BRILAC Glanzzusatz
Revision date: 10.12.2022
Issue date: 10.12.2022

EN
Page 7 / 13

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

*

Acute toxicity

Xylene

oral, LD50, Rat, male: 5,523 mg/kg
Method: EU Test B.1
inhalative (vapours), LC50, Rat, male: 6700 ppm (4 h)

ethylbenzene

oral, LD50, Rat: 3,5 mg/kg
dermal, LD50, Rabbit: 15,4 mg/kg

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

oral, LD50, Rat: 15000 mg/kg
Method: OECD 401
dermal, LD50, Rat: > 2000 mg/kg
dermal, LD50, Rabbit: > 4 mg/kg
inhalative (vapours), LC50, Rat: 13,1 mg/L (4 h)

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

oral, LD50, Rat: > 5000 mg/kg
Method: OECD 401
dermal, LD50, Rabbit: > 5000 mg/kg
Method: OECD 402
inhalative (dust and mist), LC50, Rat: > 5 mg/L (4 h)
Method: OECD 403

Skin corrosion/irritation; Serious eye damage/eye irritation

ethylbenzene

Skin, Rabbit (24 h)
Causes mild skin irritation.
eyes, Rabbit
Causes slight eye irritation

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Skin (4 h)
Causes skin irritation.
eyes
Causes serious eye irritation.

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

Skin (4 h)
Repeated exposure may cause skin dryness or cracking.
eyes
No data available

Respiratory or skin sensitisation

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Skin:
No data available (human)
Respiratory system:
No data available

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

Skin:
Based on available data, the classification criteria are not met.
Respiratory system:
No data available

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

ethylbenzene

Germ cell mutagenicity; Evaluation negative
Hamster; Mouse; ovaries
Carcinogenicity; Evaluation Carc. Cat. 2
Method: Group II B (IARC): Possible carcinogenic to humans (ethylbenzene)
human

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 170
Print date: 26.12.2022
Version: 3.0

BRILAC Glanzzusatz
Revision date: 10.12.2022
Issue date: 10.12.2022

EN
Page 8 / 13

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Lactation

No data available

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Lactation

No data available

STOT-single exposure; STOT-repeated exposure

May cause drowsiness or dizziness.

Xylene

Specific target organ toxicity (repeated exposure)

Liver and kidney damage; central nervous system

Causes damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).

Liver and kidney damage; central nervous system; hearing organs

ethylbenzene

Repeated dose toxicity, Rat: 75 mg/kg

Method OECD 407

RTECS-no.: DA0700000

Depression of central nervous system

movement disorders; headache; Vomiting

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Specific target organ toxicity (single exposure)

May cause respiratory irritation.; May cause drowsiness or dizziness.

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness.; After absorption: cardiovascular disorders, cyanosis, agitation After absorption of large quantities: Drowsiness, CNS disorders Other dangerous properties cannot be excluded.

Specific target organ toxicity (repeated exposure)

No data available

Aspiration hazard

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Aspiration hazard

Based on available data, the classification criteria are not met.

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

Aspiration hazard

Aspiration can lead to pulmonary edema and pneumonia.; May be fatal if swallowed and enters airways.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

EC No.

Designation

Classification according to

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 170
Print date: 26.12.2022
Version: 3.0

BRILAC Glanzzusatz
Revision date: 10.12.2022
Issue date: 10.12.2022

EN
Page 9 / 13

CAS No.		Regulation (EC) No 1272/2008 [CLP]
270-066-5	Fatty acid C6-C19, cobalt salt	Repr. 1B
68409-81-4		

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

Xylene

Fish toxicity, LC50, fish: 2,6 mg/L (96 h)

Method: OECD 203

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 4,6 mg/L (72 h)

Method: OECD 201

Algae toxicity, EC50, Pseudokirchneriella subcapitata: 4,6 mg/L (72 h)

Method: OECD 201

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout) (96 h)

Method: OECD 203

Daphnia toxicity, IC50, Daphnia magna: 1 mg/L (24 h)

Method: OECD 202

Algae toxicity, EC50, Selenastrum capricornutum: 2,2 mg/L (73 h)

Method: OECD 201

Daphnia toxicity, growth test (Eb-Cx) 10%“, Daphnia magna: 1,91 mg/L (21 d)

Method: OECD 211

Bacteria toxicity, NOEC, Activated sludge: 16 mg/L (28 t)

Method: OECD 301 F

ethylbenzene

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 4,2 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea) 1,8 - 2,4 mg/L (48 h)

Algae toxicity, EC50, Skeletonema costatum: 4,9 mg/L (72 h)

Algae toxicity, EC50, Pseudokirchneriella subcapitata: 7,2 mg/L (48 h)

Shellfish Toxicity, LC50, Mysidopsis bahia: > 5,2 mg/L (48 h)

Toxicity of Microorganisms, EC50, microorganisms: 96 mg/L (24 h)

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Fish toxicity, LL50:, Oncorhynchus mykiss (Rainbow trout) 10 - 30 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EL50, Daphnia magna (Big water flea) 10 - 22 mg/L (48 h)

Method: OECD 202

Algae toxicity, ELb50, Pseudokirchneriella subcapitata 4,1 - 4,6 mg/L (72 h)

Method: OECD 201

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

Daphnia toxicity, NOEC, Oncorhynchus mykiss (Rainbow trout): 0,21 mg/L (28 d)

Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

Xylene

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 4,36 mg/L (73 h)

Method: OECD 201

Fish toxicity, NOEC, fish: > 1,3 mg/L (56 d)

Daphnia toxicity, NOEC, Daphnia pulex (water flea): 1,17 mg/L (7 d)

Method: US EPA 600/4-91-003

Daphnia toxicity, EL50, Daphnia magna: 2,9 mg/L (21 d)

Method: OECD 211

Algae toxicity, EC50, Pseudokirchneriella subcapitata: 2,2 mg/L (73 h)

Method: OECD 201

Daphnia toxicity, LOEC:, Daphnia magna (Big water flea): 3,16 mg/L (21 d)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 170
Print date: 26.12.2022
Version: 3.0

BRILAC Glanzzusatz
Revision date: 10.12.2022
Issue date: 10.12.2022

EN
Page 10 / 13

Method: OECD 211
Algae toxicity, growth test (Eb-Cx) 10% , Pseudokirchneriella subcapitata: 0,72 mg/L (73 h)
Method: OECD 201

ethylbenzene

Daphnia toxicity, NOEC, Ceriodaphnia dubia (Wasserfloh): 0,96 mg/L (7 d)
Daphnia toxicity, LC50, Ceriodaphnia dubia (Wasserfloh): 3,6 mg/L (7 d)
Bacteria toxicity, EC50, Nitrosomonas sp: 96 mg/L (24 h)
Algae toxicity, NOEC, Pseudokirchneriella subcapitata: 3,4 mg/L (96 h)
Daphnia toxicity, LOEC, Ceriodaphnia dubia (Wasserfloh): 1,7 mg/L (7 d)

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Daphnia toxicity, EC50: 9 mg/L (48 h)

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

Daphnia toxicity, NOEC, Daphnia magna (Big water flea): 0,02 mg/L (21 d)
Method: OECD 211

12.2. Persistence and degradability

*

Xylene

Persistence and degradability:
Method: Rapid photochemical oxidation in air
Biodegradation: 98 percent (28 d)
Readily biodegradable (according to OECD criteria)

ethylbenzene

Biodegradation, aerobic: 70 - 80 percent (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Biodegradation: 74,7 percent (28 d)

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

Biodegradation: Evaluation Not readily biodegradable (according to OECD criteria)

12.3. Bioaccumulative potential

Xylene

Distribution coefficient n-octanol/water (log KOW): 3,49

ethylbenzene

Distribution coefficient n-octanol/water (log KOW): 3,6

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Distribution coefficient n-octanol/water (log KOW):

No data available

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

Distribution coefficient n-octanol/water (log KOW):

No data available

Bioconcentration factor (BCF)

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Bioconcentration factor (BCF): 500

high

12.4. Mobility in soil

Xylene

soil: Evaluation Absorbs slowly into the soil

Water: Evaluation Floats on the water

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

soil:

No data available

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

soil:

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 170
Print date: 26.12.2022
Version: 3.0

BRILAC Glanzzusatz
Revision date: 10.12.2022
Issue date: 10.12.2022

EN
Page 11 / 13

- 12.7. **Other adverse effects**
No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicable legislation.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1263

14.2. UN proper shipping name

Land transport (ADR/RID): Paint
Sea transport (IMDG): PAINT
Air transport (ICAO-TI / IATA-DGR): Paint

14.3. Transport hazard class(es)

Land transport (ADR/RID): KEINE GÜTER DER KLASSE 3
bei Gebinden > 450 l Klasse 3
Sea transport (IMDG)
for packages <= 450 litres: 3
Transport in accordance with the provisions of paragraph 2.3.2.5 of the
IMDG Code.
Air transport (ICAO-TI / IATA-DGR) 3

14.4. Packing group

III

14.5. Environmental hazards

Land transport (ADR/RID) not applicable
Marine pollutant not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.
Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code D/E

Sea transport (IMDG)

EmS-No. F-E, S-E

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture *

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 414

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 170
 Print date: 26.12.2022
 Version: 3.0

BRILAC Glanzzusatz
 Revision date: 10.12.2022
 Issue date: 10.12.2022

EN
 Page 12 / 13

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

15.2. **Chemical Safety Assessment** *

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
919-446-0	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	01-2119458049-33
215-535-7 1330-20-7	Xylene	01-2119488216-32
919-857-5	Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics	01-2119463258-33
202-849-4 100-41-4	ethylbenzene	01-2119489370-35
400-830-7	reaction of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl xypoly(oxyethylene)	01-0000015075-76
271-378-4 68551-44-0	FATTY C6-C19, ZINC SOAP	01-2119979093-30

SECTION 16: Other information *

Full text of classification in section 3

STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging fertility. Suspected of damaging the unborn child.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Repr. 1B / H360	Reproductive toxicity	May damage fertility.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3	Flammable liquids	On basis of test data.
STOT SE 3	STOT-single exposure	Calculation method.
Aquatic Chronic 3	Hazardous to the aquatic environment	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 170
Print date: 26.12.2022
Version: 3.0

BRILAC Glanzzusatz
Revision date: 10.12.2022
Issue date: 10.12.2022

EN
Page 13 / 13

CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version