Article Print c Versic	date:	220 19.12.2019 9.7	TURM OelfarbeRevision date: 14.12.2019ENIssue date: 14.12.2019Page 1 / 8					
SEC	TION 1: Ide	entification of t	ne substance/mixture and of the company/undertaking					
1.1.		entifiers (manufacturer/su e/designation	plier) 220 TURM Oelfarbe					
1.2.	Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses: Paint to protect surfaces							
<u>1.3</u> .	supplier (ma		afety data sheet er/downstream user/distributor) 1-5000 Aarau www.farbladen.ch					
	Dept. respo	nsible for informa	ion:					
		npetent person)						
	Emergency	y telephone num	er 145 (+41 (0)44 251 51 51)					
SEC	TION 2: Ha	zards identific	tion					
2.1.	Classificat The mixture Flam. Liq. 3 Label elem	e is classified as h 3 / H226 nents according to Reg	Regulation (EC) No 1272/2008 [CLP] azardous according to regulation (EC) No 1272/2008 [CLP]. Flammable liquids Flammable liquid and vapour. ulation (EC) No. 1272/2008 [CLP]					
23	P101 P102 P103 P210 P233 P240 P241 P242 P243 P280 P303 + P36 P370 + P37 P403 + P23 P501 Hazard con Supplement EUH208	Flamm hary statements If med Keep Read Keep Grour Use e Use n Take Wear 51 + P353 IF ON 78 In cas 35 Store Dispo mponents for lat not ap ntal Hazard infor Conta	plicable					
2.3.	Other haza No informa	ards tion available.						

SECTION 3: Composition / information on ingredients

Article No.:	220	TURM Oelfarbe		
Print date:	19.12.2019	Revision date: 14.12.2019	EN	
Version:	9.7	Issue date: 14.12.2019	Page 2 / 8	

3.2. Mixtures

Description	solvent-based alkyd resin, containing the following hazardous substances:					
Classification ac	cording to Regulation (EC) No 1272/2008 [CLP]					
EC No. CAS No. INDEX No.	REACH No. Designation classification // Remark	Wt %				
918-481-9 64742-48-9 649-327-00-6	01-2119457273-39 Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics Asp. Tox. 1 H304	25 - 50				
219-535-8 2457-01-4	01-2119983179-22 Barium bis (2-ethylhexanoate) Acute Tox. 4 H302 / Repr. 2 H361	0.5 - 1				
202-496-6 96-29-7 616-014-00-0	01-2119539477-28 2-butanone oxime Carc. 2 H351 / Acute Tox. 4 H312 / Eye Dam. 1 H318 / Skin Sens. 1 H317	< 0.5				
245-018-1 22464-99-9	Fatty acid C6-C19, zirconium Repr. 2 H361	< 0.5				
270-066-5 68409-81-4	Fatty acid C6-C19, cobalt salt Acute Tox. 4 H302 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Repr. 2 H361 / Aquatic Chronic 2 H411	< 0.5				

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed** First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water) **Unsuitable extinguishing media** strong water jet

5.2. Special hazards arising from the substance or mixture

Article No.:	220	TURM Oelfarbe		
Print date:	19.12.2019	Revision date: 14.12.2019	EN	
Version:	9.7	Issue date: 14.12.2019	Page 3 / 8	

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Article No.:	220	TURM Oelfarbe		
Print date:	19.12.2019	Revision date: 14.12.2019	EN	
Version:	9.7	Issue date: 14.12.2019	Page 4 / 8	

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance: Physical state: Colour:	Liquid refer to label
Odour:	characteristic
Odour threshold:	not applicable
pH at 20 °C:	not applicable
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	180 °C Source: Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics
Flash point:	40 °C
	Method: DIN 53213
Evaporation rate:	not applicable
flammability Burning time (s):	not applicable
Upper/lower flammability or explosive limits:	
Lower explosion limit:	0.8 Vol-% 6.5 Vol-%
Upper explosion limit:	Source: Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics
Vapour pressure at 20 °C:	0.6 mbar Source: Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics
Vapour density:	not applicable
Relative density: Density at 20 °C:	1.19 g/cm³
Solubility(ies): Water solubility (g/L) at 20 °C:	insoluble
Partition coefficient: n-octanol/water:	see section 12
Auto-ignition temperature:	240 °C Source: Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2%

Article Print d Versio	late:	220 19.12.2019 9.7	TURM Oelfarbe Revision date: 14 Issue date: 14.12		EN Page 5 / 8	
9.2.	Decompos Viscosity a Explosive Oxidising p Other infor Solid conte solvent con Organic s Water:	properties: properties: mation ent (%): ntent:		aromatics not applicable 800 - 1000 mPas not applicable not applicable 69 Wt % 31 Wt % 0 Wt %	5	
SEC	TION 10: S	tability and react	ivity			
10.1.	Reactivity	ion available.				
10.2.	Chemical s	stability	nmended regulation	ons for storage ar	nd handling. Further information on correct storage: refer to	
10.3.	•	of hazardous react from strong acids, s		strong oxidizing a	gents to avoid exothermic reactions.	
10.4.	 Conditions to avoid Hazardous decomposition byproducts may form with 			* with exposure to high temperatures.		
10.5.	 Incompatible materials not applicable 					
10.6.	 Hazardous decomposition products Hazardous decomposition byproducts may form smoke, nitrogen oxides. 			with exposure to	high temperatures, e.g.: carbon dioxide, carbon monoxide,	

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

11.1. Information on toxicological effects

Acute toxicity

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics oral, LD50, Rat: > 15000 mg/kg dermal, LD50, Rabbit: > 3160 mg/kg

Skin corrosion/irritation; Serious eye damage/eye irritation

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics Skin (4 h) Based on available data, the classification criteria are not met. eyes Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics Skin: ; evaluation Based on available data, the classification criteria are not met.

Respiratory system: ; evaluation Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics Germ cell mutagenicity; evaluation Based on available data, the classification criteria are not met. Carcinogenicity; evaluation Based on available data, the classification criteria are not met. Reproductive toxicity; evaluation Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Specific target organ toxicity (single exposure) evaluation Based on available data, the classification criteria are not met. Specific target organ toxicity (repeated exposure) evaluation Based on available data, the classification criteria are not met.

Article No.:	220	TURM Oelfarbe		
Print date:	19.12.2019	Revision date: 14.12.2019	EN	
Version:	9.7	Issue date: 14.12.2019	Page 6 / 8	

Aspiration hazard

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics Aspiration hazard; evaluation May be fatal if swallowed and enters airways.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] Do not allow to enter into surface water or drains.

12.1. Toxicity

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics Fish toxicity, LC50, Pimephales promelas (fathead minnow): 220 mg/l (96 h) Daphnia toxicity, LC50, crangon crangon: 4,3 mg/l (96 h)

12.2. Persistence and degradability

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics Biodegradation: evaluation Not readily biodegradable (according to OECD criteria)

12.3. Bioaccumulative potential

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics Partition coefficient: n-octanol/water: No further relevant information available.

12.4. Mobility in soil

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics soil:

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

14.2. UN proper shipping name

Land transport (ADR/RID):

UN 1263

Article Print d Versio	ate: 19.1	2.2019	TURM Oelfarbe Revision date: 14 Issue date: 14.12			Page 7	EN / 8	
	Sea transport (IN			PAINT				
	Air transport (ICA		GR):	Paint				
4.3.	Transport hazar	d class(es)		0				
	De alcia a anteres			3				
4.4.	Packing group			Ш				
45	Environmental h	nazards						
Ŧ. O .	Land transport (A			not applicable	2			
	Marine pollutant			not applicable				
16	Special precaut	ione for usor			•			
1.0.	· ·		abt and asfa aspt	ainara Maka	ouro that paras	no tranona	rting the pr	duct know what to do in
	case of an accide Advices on safe l	ent or leakage.	-		sule that perso		nung the pro	oduct know what to do ir
	Further information	tion						
	Land transport ((ADR/RID)						
	tunnel restriction	code		D/E				
	Sea transport (II	MDG)						
	EmS-No.			F-E. S-E				
17		k according to	o Annex II of Mar	,	BC Code			
	not applicable							
ECT	TION 15: Regula	otory inform	otion					
	•	•						
5.1.	-	nd environme	ntal regulations/l	egislation sp	ecific for the	substance	or mixture)
	EU legislation							
	Directive 2010/7 VOC-value (in g/	L): 369	strial emissions					
	National regulat							
		ment restriction	is under the Mater nent for juvenils ad					t or nursing mothers. 94/33/EC).
5.2.	Chemical Safety		of this mixture a	chemical sat	fetv assessm	ent has be	en carried	out:
	EC No.	Designa					REAC	
	CAS No. 918-481-9	Hydrocar	bons, C10-C13,	n alkanos	iso alkanos	ovelie	·20/ 01 21	19457273-39
	64742-48-9	aromatic		n-aikanes,	iso-aikaries,	Cyclic,	2/0 01-21	19407270-09
-	219-535-8 2457-01-4		is (2-ethylhexanoa	ate)			01-21	19983179-22
ECT	ION 16: Other	information						
	Full text of class	sification in se	ection 3					
	Asp. Tox. 1 / H30		Aspiration hazard			May be fata	al if swallow	ed and enters airways.
	Acute Tox. 4 / H3	302	Acute toxicity (ora	l)		Harmful if s	wallowed.	
	Repr. 2 / H361		Reproductive toxi	city				g the unborn child.
	Carc. 2 / H351		Carcinogenicity			exposure if	it is conclu	cancer (state route of sively proven that no re cause the hazard).

		other routes of exposure cause the hazard).
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging fertility. Suspected of damaging the unborn child.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.

Article Print o Versio	date:	220 19.12.2019 9.7	TURM Oelfarbe Revision date: 14.12.2019 Issue date: 14.12.2019	EN Page 8 / 8			
	Repr. 2 / H	361	Reproductive toxicity	Suspected of damaging fertility.			
	Aquatic Ch	ronic 2 / H411	Hazardous to the aquatic environment	ent Toxic to aquatic life with long lasting effects.			
	Classificat	ion procedure					
	Classification	on for mixtures and	d used evaluation method according to	pregulation (EC) No 1272/2008 [CLP]			
	Flam. Liq. 3	3	Flammable liquids	On basis of test data.			
	Abbreviati	ons and acronym	IS				
	ADR	-		tional Carriage of Dangerous Goods by Road			
	OEL	Occup	ational Exposure Limit Value				
	BLV	Biologi	ical Limit Value				
	CAS	Chemi	cal Abstracts Service				
	CLP	Classif	fication, Labelling and Packaging				
	CMR		Carcinogenic, Mutagenic and Reprotoxic				
	DIN		German Institute for Standardization / German industrial standard				
	DNEL		Derived No-Effect Level				
	EAKV		ean Waste Catalogue Directive				
	EC		ve Concentration				
	EC	•	ean Community				
	EN		European Standard				
	IATA-DGR		nternational Air Transport Association – Dangerous Goods Regulations				
	IBC Code		nternational Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk				
	ICAO-TI		International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous				
		Goods					
	IMDG Code		ational Maritime Code for Dangerous G				
	ISO LC		ational Organization for Standardizatio Concentration	I			
	LD	Lethal					
	MARPOL			tion for the Prevention of Pollution from Ships			
	OECD		isation for Economic Cooperation and				
	PBT		ent, bioaccumulative, toxic	Development			
	PNEC		ted No Effect Concentration				
	REACH		ration, Evaluation, Authorisation and F	estriction of Chemicals			
	RID		ations concerning the International Car				
	UN	•	Nations				
	VOC		e Organic Compounds				
	vPvB		ersistent and very bioaccumulative				
	Further inf	ormation	-				

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version