

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

VFL
Vismara Farbladen

Article No.: 317 BRICATOL Tank-Innenschutzlack
Print date: 26.12.2022 Revision date: 10.12.2022 EN
Version: 8.0 Issue date: 10.12.2022 Page 1 / 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. **product identifiers**

Article No. (manufacturer/supplier) 317
Trade name/designation BRICATOL Tank-Innenschutzlack

1.2. **Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses:

Coating material to protecting surfaces

1.3. **Details of the supplier of the safety data sheet**

supplier (manufacturer/importer/downstream user/distributor)

Vismara Unternehmungen CH-5000 Aarau www.farbladen.ch

Department responsible for information:

laboratory Manager

E-mail (competent person)

info@knuchel.ch

1.4. **Emergency telephone number**

Emergency telephone number 145 (+41 (0)44 251 51 51)

SECTION 2: Hazards identification

2.1. **Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Muta. 2 / H341	Germ cell mutagenicity	Suspected of causing genetic defects.

2.2. **Label elements**

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H341 Suspected of causing genetic defects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves and eye/face protection.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/attention.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 317 BRICATOL Tank-Innenschutzlack
 Print date: 26.12.2022 Revision date: 10.12.2022 EN
 Version: 8.0 Issue date: 10.12.2022 Page 2 / 10

P310 Immediately call a POISON CENTER or doctor/ physician.
 P332 + P313 If skin irritation occurs: Get medical advice/attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
 P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Keep locked up.
 P501 Dispose of contents/container to industrial incineration plant.

Hazard components for labelling

butan-1-ol
 Phenol

Supplemental hazard information

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
 EUH208 Contains formaldehyde. May produce an allergic reaction.

2.3. **Other hazards**

No information available.

SECTION 3: Composition/information on ingredients

3.2. **Mixtures**

Description solvent-based alkyd resin, containing the following hazardous substances:

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification // Remark	weight-%
200-751-6 71-36-3 603-004-00-6	01-2119484630-38 butan-1-ol Acute Tox. 4 H302 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / STOT SE 3 H335 / STOT SE 3 H336 / Flam. Liq. 3 H226 Acute toxicity estimate (ATE), ATE (oral): 2292 mg/kg bw	1 - 5
203-632-7 108-95-2 604-001-00-2	01-2119471329-32 Phenol Muta. 2 H341 / Acute Tox. 3 H331 / Acute Tox. 3 H311 / Acute Tox. 3 H301 / STOT RE 2 H373 / Skin Corr. 1B H314 Specific concentration limit (SCL): Skin Corr. 1B H314 >= 3 / Skin Irrit. 2 H315 >= 1 / Eye Irrit. 2 H319 >= 1	1 - 5
200-001-8 50-00-0 605-001-00-5	01-2119488953-20 formaldehyde Carc. 1B H350 / Muta. 2 H341 / Acute Tox. 3 H301 / Acute Tox. 3 H311 / Acute Tox. 3 H331 / Skin Corr. 1B H314 / Skin Sens. 1 H317 Specific concentration limit (SCL): Skin Corr. 1B H314 >= 25 / Skin Irrit. 2 H315 >= 5 / Eye Irrit. 2 H319 >= 5 / STOT SE 3 H335 >= 5 / Skin Sens. 1 H317 >= 0.2	0.05 - 0.1

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. **Description of first aid measures**

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.:	317	BRICATOL Tank-Innenschutzlack	
Print date:	26.12.2022	Revision date: 10.12.2022	EN
Version:	8.0	Issue date: 10.12.2022	Page 3 / 10

medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 317 BRICATOL Tank-Innenschutzlack
Print date: 26.12.2022 Revision date: 10.12.2022 EN
Version: 8.0 Issue date: 10.12.2022 Page 4 / 10

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

butan-1-ol

Index No. 603-004-00-6 / EC No. 200-751-6 / CAS No. 71-36-3

WEL, STEL: 154 mg/m³; 50 ppm

Remark: (may be absorbed through the skin)

Phenol

Index No. 604-001-00-2 / EC No. 203-632-7 / CAS No. 108-95-2

WEL, TWA: 7.8 mg/m³; 2 ppm

WEL, STEL: 16 mg/m³; 4 ppm

Remark: (may be absorbed through the skin)

formaldehyde

Index No. 605-001-00-5 / EC No. 200-001-8 / CAS No. 50-00-0

WEL, TWA: 2.5 mg/m³; 2 ppm

WEL, STEL: 2.5 mg/m³; 2 ppm

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

butan-1-ol

Index No. 603-004-00-6 / EC No. 200-751-6 / CAS No. 71-36-3

DNEL long-term oral (repeated), Workers: 3,125 mg/kg

DNEL acute inhalative (local), Workers: 310 mg/m³

DNEL acute inhalative (systemic), Workers: 310 mg/m³

DNEL long-term inhalative (local), Workers: 310 mg/m³

DNEL long-term inhalative (systemic), Workers: 310 mg/m³

DNEL long-term oral (local): 3,125 mg/kg

DNEL long-term inhalative (local), Consumer: 55 mg/m³

DNEL long-term inhalative (systemic), Consumer: 55 mg/m³

PNEC:

butan-1-ol

Index No. 603-004-00-6 / EC No. 200-751-6 / CAS No. 71-36-3

PNEC aquatic, freshwater: 0,082 mg/L

PNEC aquatic, marine water: 0,0082 mg/L

PNEC aquatic, intermittent release: 2,25 mg/L

PNEC sediment, freshwater: 0,178 mg/kg

PNEC sediment, marine water: 0,0178 mg/kg

PNEC, soil: 0,015 mg/kg

PNEC sewage treatment plant (STP): 2476 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 317
Print date: 26.12.2022
Version: 8.0

BRICATOL Tank-Innenschutzlack
Revision date: 10.12.2022
Issue date: 10.12.2022

EN
Page 5 / 10

must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	refer to label
Odour:	characteristic
Odour threshold:	not applicable
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	78 °C Source: Ethanol
Flammability:	Highly flammable liquid and vapour.
Lower and upper explosion limit:	
Lower explosion limit:	3.5 Vol-%
Upper explosion limit:	15 Vol-% Source: Ethanol
Flash point:	13 °C Method: DIN 53213
Auto-ignition temperature:	360 °C Source: butan-1-ol
Decomposition temperature:	not applicable
pH at 20 °C:	not applicable
Cinematic viscosity (40°C):	< 400 mm²/s
Viscosity at 20 °C:	700 - 1200 mPas
Solubility(ies):	
Water solubility at 20 °C:	partially soluble
Partition coefficient: n-octanol/water:	see section 12
Vapour pressure at 20 °C:	59 mbar Source: Ethanol
Density and/or relative density:	
Density at 20 °C:	1.12 g/cm³
Relative vapour density:	not applicable
particle characteristics:	not applicable

9.2. Other information

Solid content:	56 weight-%
solvent content:	
Organic solvents:	41 weight-%

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 317
Print date: 26.12.2022
Version: 8.0

BRICATOL Tank-Innenschutzlack
Revision date: 10.12.2022
Issue date: 10.12.2022

EN
Page 6 / 10

Water: 2 weight-%

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

butan-1-ol

oral, LD50, Rat: 2292 mg/kg

Method: OECD 401

Harmful if swallowed.

dermal, LD50, Rabbit: 3430 mg/kg

Method: OECD 402

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye damage.

butan-1-ol

Skin, Rabbit (4 h)

Method: BASF - Test

eyes, Rabbit

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Suspected of causing genetic defects.

butan-1-ol

teratogenicity, oral

Method: NOAEL

Rat; 1.454 mg/kg; Toxicological effects in dams

teratogenicity, oral

Method: NOAEL

Rat; 5.654 mg/kg

teratogenicity, inhalative

Method: NOAEL

Rat; 10.8 mg/l; Toxicological effects in dams

teratogenicity, inhalative

Method: NOAEL

Rat; 24.7 mg/l

Reproductive toxicity, inhalative

Method: NOAEL

Rat; 18.5 mg/l; parents

Reproductive toxicity, inhalative

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 317 BRICATOL Tank-Innenschutzlack
Print date: 26.12.2022 Revision date: 10.12.2022
Version: 8.0 Issue date: 10.12.2022

EN
Page 7 / 10

Method: NOAEL
Mouse; 18.5 mg/l; F1

STOT-single exposure; STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

butan-1-ol
Aspiration hazard

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

EC No. CAS No.	Designation	Classification according to Regulation (EC) No 1272/2008 [CLP]
200-001-8 50-00-0	formaldehyde	Carc. 1B

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]
Do not allow to enter into surface water or drains.

12.1. Toxicity

butan-1-ol
Fish toxicity, LC50, Pimephales promelas (fathead minnow): 1376 mg/L (96 h)
Method: OECD 203
Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1328 mg/L (48 h)
Method: OECD 202
Algae toxicity, EC50, Selenastrum capricornutum: 225 mg/L
Method: OECD 201
literature value
Bacteria toxicity, EC10, Pseudomonas putida: 2476 mg/L (17 h)
Method: DIN 38412

Long-term Ecotoxicity

butan-1-ol
Daphnia toxicity, NOEL, Daphnia magna (Big water flea): 4,1 mg/L (21 d)
Method: OECD 211

12.2. Persistence and degradability

butan-1-ol
Biodegradation: 92 percent (20 d); Evaluation Readily biodegradable (according to OECD criteria)
aerobic.; Activated sludge; Biochemical oxygen demand

12.3. Bioaccumulative potential

butan-1-ol
Partition coefficient: n-octanol/water:
Bioaccumulation is not to be expected.
Distribution coefficient n-octanol/water (log KOW): 0,88

12.4. Mobility in soil

butan-1-ol
Mobility in soil:
The substance does not evaporate from the water surface into the atmosphere.; Does not adsorb to the ground.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 317 BRICATOL Tank-Innenschutzlack
Print date: 26.12.2022 Revision date: 10.12.2022 EN
Version: 8.0 Issue date: 10.12.2022 Page 8 / 10

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicable legislation.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1263

14.2. UN proper shipping name

Land transport (ADR/RID): Paint
Sea transport (IMDG): PAINT
Air transport (ICAO-TI / IATA-DGR): Paint

14.3. Transport hazard class(es)

3

14.4. Packing group

Land transport (ADR/RID):
for packages > 450 litres: III
II
Sea transport (IMDG): III
for packages > 450 litres: II
Air transport (ICAO-TI / IATA-DGR): III
for packages > 30 litres: II

14.5. Environmental hazards

Land transport (ADR/RID) not applicable
Marine pollutant not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code E
for packages > 450 litres: D/E

Sea transport (IMDG)

EmS-No. F-E, S-E

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 317
Print date: 26.12.2022
Version: 8.0

BRICATOL Tank-Innenschutzlack
Revision date: 10.12.2022
Issue date: 10.12.2022

EN
Page 9 / 10

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 473

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
200-751-6 71-36-3	butan-1-ol	01-2119484630-38
203-632-7 108-95-2	Phenol	01-2119471329-32
200-001-8 50-00-0	formaldehyde	01-2119488953-20

SECTION 16: Other information

Full text of classification in section 3

Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Muta. 2 / H341	Germ cell mutagenicity	Suspected of causing genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Acute Tox. 3 / H331	Acute toxicity (inhalative)	Toxic if inhaled.
Acute Tox. 3 / H311	Acute toxicity (dermal)	Toxic in contact with skin.
Acute Tox. 3 / H301	Acute toxicity (oral)	Toxic if swallowed.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Skin Corr. 1B / H314	Skin corrosion/irritation	Causes severe skin burns and eye damage.
Carc. 1B / H350	Carcinogenicity	May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2	Flammable liquids	On basis of test data.
Skin Irrit. 2	Skin corrosion/irritation	Calculation method.
Eye Dam. 1	Serious eye damage/eye irritation	Calculation method.
Muta. 2	Germ cell mutagenicity	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 317 BRICATOL Tank-Innenschutzlack
Print date: 26.12.2022 Revision date: 10.12.2022 EN
Version: 8.0 Issue date: 10.12.2022 Page 10 / 10

CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.