Article Print d Versio	ate:	579 27.12.2022 2.0	DUROXIL Siloxan-Fassadenfarbe Revision date: 10.12.2022 EN Issue date: 10.12.2022 Page 1 / 8	
SEC	TION 1: Id	entification of th	he substance/mixture and of the company/undertaking	
1.1.		l entifier (manufacturer/sup e/designation	oplier) 579 DUROXIL Siloxan-Fassadenfarbe	
1.2.		-	the substance or mixture and uses advised against	
<u>1.3</u> .	Details of the	ne supplier of the s	afety data sheet	
	•••	-	ter/downstream user/distributor) H-5000 Aarau www.farbladen.ch	
	laboratory	nt responsible for Manager npetent person)	r information:	
1.4.	Emergenc	y telephone number / telephone number	ber	
SEC	TION 2: Ha	azards identifica	ation	
2.1.		tion of the substa		
			Regulation (EC) No 1272/2008 [CLP]	
	The mixtur	e is classified as n	not hazardous according to regulation (EC) No 1272/2008 [CLP].	
	Labelling Hazard pic		julation (EC) No. 1272/2008 [CLP]	
	Hazard sta		plicable	
		nary statements		
	P101 P102 P103	Keep o	lical advice is needed, have product container or label at hand. out of reach of children. carefully and follow all instructions.	
	Hazard co	mponents for lab not ap	pelling plicable	
	Suppleme EUH211 EUH208	Contai	ng! Hazardous respirable droplets may be formed when sprayed. Do not breathe spra ins 1,2-benzisothiazol-3(2H)-one; reaction mass of 5-chloro-2- methyl-2H-isothiazol-3 hyl-2H-isothiazol-3- one (3:1); MIT (2-methyl-(2H)-isothiazol-3-one). May produce an a	3-one and
	EUH210		/ data sheet available on request.	
2.3.	Other haz	-		
	No informa	tion available.		
SEC	TION 3: Co	omposition/info	rmation on ingredients	
3.2.	Mixtures			
	Descriptio	n waterb	porne acrylic dispersion paint, containing the following hazardous substances:	
	EC No. CAS No.	REAC Desig	nation weig	ght-%
	Index No. 203-473-3		ification: // Remark 19456816-28	

Additional information

Article No.:	579	DUROXIL Siloxan-Fassadenfarbe		
Print date:	27.12.2022	Revision date: 10.12.2022	EN	
Version:	2.0	Issue date: 10.12.2022	Page 2 / 8	

Full text of H-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed** First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in

Article No.:	579	DUROXIL Siloxan-Fassadenfarbe		
Print date:	27.12.2022	Revision date: 10.12.2022	EN	
Version:	2.0	Issue date: 10.12.2022	Page 3 / 8	

containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

ethanediol Index No. 603-027-00-1 / EC No. 203-473-3 / CAS No. 107-21-1

WEL, TWA: 52 mg/m3; 20 ppm

WEL, STEL: 104 mg/m3; 40 ppm Remark: (vapour, may be absorbed through the skin)

WEL, TWA: 10 mg/m3

Remark: (may be absorbed through the skin)

Additional information

TWA : Long-term occupational exposure limit value STEL : short-term occupational exposure limit value Ceiling : peak limitation

DNEL:

ethanediol

Index No. 603-027-00-1 / EC No. 203-473-3 / CAS No. 107-21-1 DNEL long-term dermal (systemic), Workers: 106 mg/kg bw/day DNEL long-term inhalative (local), Workers: 35 mg/m³ DNEL long-term dermal (systemic), Consumer: 53 mg/kg DNEL long-term inhalative (local), Consumer: 7 mg/m³

PNEC:

ethanediol

Index No. 603-027-00-1 / EC No. 203-473-3 / CAS No. 107-21-1 PNEC aquatic, freshwater: 10 mg/L PNEC aquatic, marine water: 1 mg/L PNEC aquatic, intermittent release: 10 mg/L PNEC sediment, freshwater: 20,9 mg/kg PNEC, soil: 1,53 mg/kg

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

Personal protection equipment

Respiratory protection

Not applicable.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material 0,4 mm Breakthrough time: 30 min

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin: Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Article No.:	579	DUROXIL Siloxan-Fassadenfarbe		
Print date:	27.12.2022	Revision date: 10.12.2022	EN	
Version:	2.0	Issue date: 10.12.2022	Page 4 / 8	
			•	

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear suitable protective clothing and gloves.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

	Physical state: Colour:	Liquid refer to label
	Odour:	characteristic
	Odour threshold:	not applicable
	Melting point/freezing point:	not applicable
	Initial boiling point and boiling range:	100 °C
		Source: PH EN 501166 GEFBEZ@tr4000
	Flammability	not applicable
	Lower and upper explosion limit:	
	Lower explosion limit:	0.8 Vol-%
	Upper explosion limit:	not applicable
	Flash point:	not applicable
	Auto-ignition temperature:	410 °C
		Source: ethanediol
	Decomposition temperature:	not applicable
	pH at 20 °C:	not applicable
	Cinematic viscosity (40°C):	2780.09 mm²/s
	Viscosity at 20 °C:	4000 - 5000 mPas
	Solubility(ies):	
	Water solubility at 20 °C:	partially soluble
	Partition coefficient: n-octanol/water:	see section 12
	Vapour pressure at 20 °C:	23 mbar Source: PH EN 501166 GEFBEZ@tr4000
	Density and/or relative density:	
	Density at 20 °C:	1.44 g/cm³
	Relative vapour density:	not applicable
	particle characteristics:	not applicable
2.	Other information	
	Solid content:	60 weight-%
	solvent content:	
	Organic solvents:	2 weight-%
	Water:	38 weight-%
5	TION 10: Stability and reactivity	

SECTION 10: Stability and reactivity

10.1. Reactivity

9.2.

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Article No.:	579	DUROXIL Siloxan-Fassadenfarbe		
Print date:	27.12.2022	Revision date: 10.12.2022	EN	
Version:	2.0	Issue date: 10.12.2022	Page 5 / 8	

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures. e.g.: carbon dioxide. carbon monoxide. smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

ethanediol

inhalative (dust and mist). LC50. Rat: > 2.5 mg/L (6 h) dermal, LD50, Mouse: > 3500 mg/kg

Skin corrosion/irritation; Serious eye damage/eye irritation

ethanediol Skin (4 h)

Respiratory or skin sensitisation

ethanediol Skin: No sensitizing effect Respiratory system: No sensitizing effect

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

ethanediol

Germ cell mutagenicity: Evaluation Did not show any mutagenic effects in animal experiments. Tests with bacterial or mammalian cell cultures showed no evidence of mutagenic activity.; Some structurally similar substances showed mutagenic effects. Carcinogenicity Didn't show any carcinogenic effects in animal tests.

Reproductive toxicity

No effect on fertility in animal studies.

teratogenicity; Evaluation Ingestion of excessive amounts by pregnant animals leads to toxic effects in the dam and fetus.

STOT-single exposure; STOT-repeated exposure

ethanediol

Specific target organ toxicity (single exposure) Specific target organ toxicity (single exposure), Irritation Irritating to respiratory system. Specific target organ toxicity (repeated exposure) Evaluation Causes damage to organs through prolonged or repeated exposure. kidneys; Ingestion

Aspiration hazard

ethanediol

Aspiration hazard

no classification

Experiences with human exposure.: Evaluation Organic solvent, avoid repeated exposure.

Chronic exposure damages the brain and the central nervous system. ; Kidney damage is possible.; Continued exposure may cause chronic effects. Ingestion is harmful to health.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of

natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

11.2. Information on other hazards

Endocrine disrupting properties No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] Do not allow to enter into surface water or drains.

12.1. Toxicity

ethanediol

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 72860 mg/L (96 h) Method: Static test Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 100 mg/L (48 h) Method: OECD 202 Algae toxicity, ErC50, Selenastrum capricornutum: 6500 mg/L 13000 (96 h) Bacteria toxicity, EC20, Activated sludge: > 1995 mg/L (30 min.) Method: ISO 8192

Long-term Ecotoxicity

ethanediol

Daphnia toxicity, NOEC, Ceriodaphnia dubia (Wasserfloh): 8590 mg/L (7 d) Fish toxicity, NOEC, Pimephales promelas (fathead minnow): 15380 mg/L (7 d)

12.2. Persistence and degradability

ethanediol

Persistence and degradability: Evaluation Keine signifikante Hydrolyse (Related to: Water) Biodegradation: 90 - 100 percent (10 d) Method: OECD 301A Activated sludge; Related to: Chemical oxygen demand; Biochemical oxygen demand (BOD): 1245 mg/g

12.3. Bioaccumulative potential

ethanediol

Distribution coefficient n-octanol/water (log KOW): -1,36 Bioaccumulation is not to be expected.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

ethanediol

Air: Evaluation The substance does not evaporate from the water surface into the atmosphere. soil: Evaluation A binding to the solid ground phase is not to be expected.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Article Print d Versio	ate:	579 27.12.2022 2.0	DUROXIL Siloxan-Fassadenfarbe Revision date: 10.12.2022EN Page 7 / 8			
	List of pro 080112		s/waste designations in accordance with EWC int and varnish other than those mentioned in 08 01 11			
		e disposal / Packa				
	Recomme	ndation	ay be recycled. Vessels not properly emptied are special waste.			
SECT	FION 14: T	ransport inform	tion			
	ICAO/IATA).	ed as dangerous according to international transport regulations (ADR/RID, IMD			
	-	-	of this transport regulation.			
14.1.	UN numbe	r or ID number	not applicable			
14.2.	UN proper	shipping name				
14.3.	Transport	hazard class(es)				
			not applicable			
14.4.	Packing gi	oup	not applicable			
14.5.		ental hazards				
	-	port (ADR/RID)	not applicable			
	Marine poll		not applicable			
14.6.		ecautions for user				
	Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage. Advices on safe handling: see parts 6 - 8					
	Further inf	ormation				
	Land trans	port (ADR/RID)				
		riction code	-			
	Sea transp	ort (IMDG)				
	EmS-No.	, ,	not applicable			
14.7.	Maritime to	ansport in bulk a	cording to IMO instruments			
	No transpo	rt as bulk according	IBC - Code.			
SECT	ΓΙΟΝ 15: R	egulatory inform	ation			
15.1.	Safety, hea	alth and environm	ntal regulations/legislation specific for the substance or mixture			
	EU legislation					
	Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive] VOC-value (in g/L): 33					
	National re	gulations				
	Restrictions of occupation					
	applicable.		ons under the Maternity Protection Directive 92/85/EEC or stricter national regulations, ment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or strict			
15 0	national reg	gulations, if applica	le.			
10.2.	For the fol	-	of this mixture a chemical safety assessment has been carried out:			
	EC No. CAS No.	Design				
-	203-473-3 107-21-1	ethaneo	ol 01-2119456816-28			

SECTION 16: Other information

Article No.: Print date: Version:	579 27.12.2022 2.0	DUROXIL Siloxan-Fassadenfarbe Revision date: 10.12.2022 Issue date: 10.12.2022	EN Page 8 / 8
Full tex	t of classification i	n section 3	
Acute T	ox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
STOT RE 2 / H373		STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it

is conclusively proven that no other routes of exposure cause the hazard).

Abbreviations and acronyms

Abbiotiationo an	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous
	Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version