

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 67 BRILALIT Venti-Grund 3 in 1
Print date: 19.12.2019 Revision date: 14.12.2019 EN
Version: 7.7 Issue date: 14.12.2019 Page 1 / 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. product identifiers

Article No. (manufacturer/supplier) 67
Trade name/designation BRILALIT Venti-Grund 3 in 1
LH-67

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Paint to protect surfaces

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

Vismara Unternehmungen CH-5000 Aarau www.farbladen.ch

Dept. responsible for information:

laboratory Manager
E-mail (competent person)

1.4. Emergency telephone number

Emergency telephone number 145 (+41 (0)44 251 51 51)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Warning

Hazard statements

H226 Flammable liquid and vapour.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P273 Avoid release to the environment.
P280 Wear protective gloves and eye/face protection.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.
P403 + P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container to industrial incineration plant.

Hazard components for labelling

not applicable

Supplemental Hazard information (EU)

EUH208 Contains 2-butanone oxime; (R)-p-mentha-1,8-diene; Fatty acid C6-C19, cobalt salt. May produce an

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 67
Print date: 19.12.2019
Version: 7.7

BRILALIT Venti-Grund 3 in 1
Revision date: 14.12.2019
Issue date: 14.12.2019

EN
Page 2 / 10

allergic reaction.

2.3. Other hazards

No information available.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Description solvent-based alkyd resin, containing the following hazardous substances:

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Designation classification // Remark	Wt %
919-446-0 64742-82-1 649-330-00-2	01-2119458049-33 Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha STOT SE 3 H336 / Asp. Tox. 1 H304 / Aquatic Chronic 2 H411 / Flam. Liq. 3 H226	12.5 - 20
918-481-9 64742-48-9 649-327-00-6	01-2119457273-39 Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics Asp. Tox. 1 H304	2.5 - 5
202-496-6 96-29-7 616-014-00-0	01-2119539477-28 2-butanone oxime Carc. 2 H351 / Acute Tox. 4 H312 / Eye Dam. 1 H318 / Skin Sens. 1 H317	0.5 - 1
227-813-5 5989-27-5 601-029-00-7	01-2119529223-47 (R)-p-mentha-1,8-diene Flam. Liq. 3 H226 / Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	0.5 - 1
271-378-4 68551-44-0	01-2119979093-30 FATTY C6-C19, ZINC SOAP Eye Irrit. 2 H319 / Repr. 2 H361 / Asp. Tox. 1 H304 / Aquatic Chronic 3 H412	< 0.5
270-066-5 68409-81-4	Fatty acid C6-C19, cobalt salt Acute Tox. 4 H302 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Repr. 2 H361 / Aquatic Chronic 2 H411	< 0.5
245-018-1 22464-99-9	Fatty acid C6-C19, zirconium Repr. 2 H361	< 0.5

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 67
Print date: 19.12.2019
Version: 7.7

BRILALIT Venti-Grund 3 in 1
Revision date: 14.12.2019
Issue date: 14.12.2019

EN
Page 3 / 10

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSIVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 67 BRILALIT Venti-Grund 3 in 1
Print date: 19.12.2019 Revision date: 14.12.2019 EN
Version: 7.7 Issue date: 14.12.2019 Page 4 / 10

from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

not applicable

DNEL:

Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha
INDEX No. 649-330-00-2 / EC No. 919-446-0 / CAS No. 64742-82-1

DNEL long-term dermal (local), Workers: 44 mg/kg
DNEL long-term dermal (systemic), Workers: 44 mg/kg
DNEL acute inhalative (local), Workers: 570 mg/m³
DNEL acute inhalative (systemic), Workers: 570 mg/m³
DNEL long-term inhalative (local), Workers: 330 mg/m³
DNEL long-term inhalative (systemic), Workers: 330 mg/m³
DNEL long-term oral (repeated), Consumer: 26 mg/kg
DNEL long-term dermal (local), Consumer: 26 mg/kg
DNEL long-term dermal (systemic), Consumer: 26 mg/kg
DNEL acute inhalative (local), Consumer: 570 mg/m³
DNEL long-term inhalative (local), Consumer: 71 mg/m³
DNEL long-term inhalative (systemic), Consumer: 71 mg/m³

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)
Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state:

Liquid

Colour:

refer to label

Odour:

characteristic

Odour threshold:

not applicable

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 67
Print date: 19.12.2019
Version: 7.7

BRILALIT Venti-Grund 3 in 1
Revision date: 14.12.2019
Issue date: 14.12.2019

EN
Page 5 / 10

pH at 20 °C:	not applicable
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	162 °C Source: Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha
Flash point:	40 °C Method: DIN 53213
Evaporation rate:	not applicable
flammability	
Burning time (s):	not applicable
Upper/lower flammability or explosive limits:	
Lower explosion limit:	0.7 Vol-%
Upper explosion limit:	6.5 Vol-% Source: Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics
Vapour pressure at 20 °C:	3.7 mbar Source: Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha
Vapour density:	not applicable
Relative density:	
Density at 20 °C:	1.53 g/cm³
Solubility(ies):	
Water solubility (g/L) at 20 °C:	insoluble
Partition coefficient: n-octanol/water:	see section 12
Auto-ignition temperature:	240 °C Source: Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics
Decomposition temperature:	not applicable
Viscosity at °C:	1150 - 1200 mPas
Explosive properties:	not applicable
Oxidising properties:	not applicable
9.2. Other information	
Solid content (%):	80 Wt %
solvent content:	
Organic solvents:	19 Wt %
Water:	0 Wt %
Solvent separation test (%):	< 3 Wt % (ADR/RID)

SECTION 10: Stability and reactivity

- 10.1. **Reactivity**
No information available.
- 10.2. **Chemical stability**
Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.
- 10.3. **Possibility of hazardous reactions**
Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.
- 10.4. **Conditions to avoid**
Hazardous decomposition byproducts may form with exposure to high temperatures. *
- 10.5. **Incompatible materials**
not applicable
- 10.6. **Hazardous decomposition products**
Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 67
Print date: 19.12.2019
Version: 7.7

BRILALIT Venti-Grund 3 in 1
Revision date: 14.12.2019
Issue date: 14.12.2019

EN
Page 6 / 10

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

11.1. Information on toxicological effects

*

Acute toxicity

(R)-p-mentha-1,8-diene

oral, LD50, Rat: 4400 mg/kg

dermal, LD50, Rabbit: 5000 mg/kg

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

oral, LD50, Rat: > 15000 mg/kg

dermal, LD50, Rabbit: > 3160 mg/kg

Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha

oral, LD50, Rat: 15000 mg/kg

Method: OECD 401

dermal, LD50, Rat: > 2000 mg/kg

dermal, LD50, Rabbit: > 4 mg/kg

inhalative (vapours), LC50, Rat: 13,1 mg/l (4 h)

Skin corrosion/irritation; Serious eye damage/eye irritation

(R)-p-mentha-1,8-diene

Skin (4 h)

Causes skin irritation.

eyes

Not to be classified as severe eye damage or eye irritation.

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Skin (4 h)

Based on available data, the classification criteria are not met.

eyes

Based on available data, the classification criteria are not met.

Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha

Skin (4 h)

Causes skin irritation.

eyes

Causes serious eye irritation.

Respiratory or skin sensitisation

(R)-p-mentha-1,8-diene

Skin: ; evaluation May cause sensitization by skin contact.

May cause an allergic skin reaction.

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Skin: ; evaluation Based on available data, the classification criteria are not met.

Respiratory system: ; evaluation Based on available data, the classification criteria are not met.

Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha

Skin:

No data available (human)

Respiratory system:

No data available

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

(R)-p-mentha-1,8-diene

Germ cell mutagenicity; evaluation Not to be classified as germ cell mutagen (mutagen).

Carcinogenicity; evaluation Does not qualify as a carcinogen.

Reproductive toxicity; evaluation Does not qualify as a carcinogen.

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Germ cell mutagenicity; evaluation Based on available data, the classification criteria are not met.

Carcinogenicity; evaluation Based on available data, the classification criteria are not met.

Reproductive toxicity; evaluation Based on available data, the classification criteria are not met.

Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha

Germ cell mutagenicity

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 67
Print date: 19.12.2019
Version: 7.7

BRILALIT Venti-Grund 3 in 1
Revision date: 14.12.2019
Issue date: 14.12.2019

EN
Page 7 / 10

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Lactation

No data available

STOT-single exposure; STOT-repeated exposure

(R)-p-mentha-1,8-diene

Specific target organ toxicity (single exposure) evaluation Not to be classified as specific target organ toxic (single exposure).

Specific target organ toxicity (repeated exposure) evaluation Not to be classified as specific target organ toxic (repeated exposure).

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Specific target organ toxicity (single exposure) evaluation Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure) evaluation Based on available data, the classification criteria are not met.

Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha

Specific target organ toxicity (single exposure)

May cause respiratory irritation.; May cause drowsiness or dizziness.

Aspiration hazard

(R)-p-mentha-1,8-diene

Aspiration hazard; evaluation Not to be classified as aspirational.

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Aspiration hazard; evaluation May be fatal if swallowed and enters airways.

Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

(R)-p-mentha-1,8-diene

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 0,7 mg/l (96 h)

Daphnia toxicity, EC50: 17 mg/l (48 h)

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 220 mg/l (96 h)

Daphnia toxicity, LC50, crangon crangon: 4,3 mg/l (96 h)

Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha

Fish toxicity, LL50., Oncorhynchus mykiss (Rainbow trout) 10 - 30 mg/l (96 h)

Method: OECD 203

Daphnia toxicity, EL50, Daphnia magna (Big water flea) 10 - 22 mg/l (48 h)

Method: OECD 202

Algae toxicity, ELb50, Pseudokirchneriella subcapitata 4,1 - 4,6 mg/l (72 h)

Method: OECD 201

Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 67
Print date: 19.12.2019
Version: 7.7

BRILALIT Venti-Grund 3 in 1
Revision date: 14.12.2019
Issue date: 14.12.2019

EN
Page 8 / 10

Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha
Daphnia toxicity, EC50: 9 mg/l (48 h)

12.2. Persistence and degradability

(R)-p-mentha-1,8-diene

Biodegradation: > 40 percent (14 d); evaluation Readily biodegradable (according to OECD criteria).

Process: biotic/abiotic

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Biodegradation: evaluation Not readily biodegradable (according to OECD criteria)

Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha

Biodegradation: 74,7 percent (28 d)

12.3. Bioaccumulative potential

(R)-p-mentha-1,8-diene

Distribution coefficient n-octanol/water (log KOW): 4,57 ; evaluation The substance meets the criterion "very bioaccumulative".

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Partition coefficient: n-octanol/water:

No further relevant information available.

Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha

Distribution coefficient n-octanol/water (log KOW):

No data available

Bioconcentration factor (BCF)

Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha

Bioconcentration factor (BCF): 500

high

12.4. Mobility in soil

(R)-p-mentha-1,8-diene

soil:

No data available

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

soil:

No further relevant information available.

Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha

soil:

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

UN 1263

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: 67 BRILALIT Venti-Grund 3 in 1
 Print date: 19.12.2019 Revision date: 14.12.2019 EN
 Version: 7.7 Issue date: 14.12.2019 Page 9 / 10

- 14.2. UN proper shipping name**
 Land transport (ADR/RID): Paint
 Sea transport (IMDG): PAINT
 Air transport (ICAO-TI / IATA-DGR): Paint
- 14.3. Transport hazard class(es)**
 Land transport (ADR/RID): KEINE GÜTER DER KLASSE 3
 bei Gebinden > 450 l Klasse 3
 Sea transport (IMDG)
 for packages < 30 litres: 3
 Transport in accordance with the provisions of paragraph 2.3.2.5 of the
 IMDG Code.
 Air transport (ICAO-TI / IATA-DGR) 3
- 14.4. Packing group**
 III
- 14.5. Environmental hazards**
 Land transport (ADR/RID) not applicable
 Marine pollutant not applicable
- 14.6. Special precautions for user**
 Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in
 case of an accident or leakage.
 Advices on safe handling: see parts 6 - 8
- Further information**
- Land transport (ADR/RID)**
 tunnel restriction code D/E
- Sea transport (IMDG)**
 EmS-No. F-E, S-E
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**
 not applicable

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**
- EU legislation**
Directive 2010/75/EU on industrial emissions
 VOC-value (in g/L): 305
- National regulations**
Restrictions of occupation
 Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
 Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

- 15.2. Chemical Safety Assessment**
For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
919-446-0 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy; Low boilingpoint hydrogen treated naphtha	01-2119458049-33
918-481-9 64742-48-9	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics	01-2119457273-39
271-378-4 68551-44-0	FATTY C6-C19, ZINC SOAP	01-2119979093-30

SECTION 16: Other information

Full text of classification in section 3

STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.:	67	BRILALIT Venti-Grund 3 in 1	
Print date:	19.12.2019	Revision date: 14.12.2019	EN
Version:	7.7	Issue date: 14.12.2019	Page 10 / 10

Carc. 2 / H351	Carcinogenicity	Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard). Harmful in contact with skin.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic organisms.
Aquatic Chronic 1 / H410	Hazardous to the aquatic environment	Very toxic to aquatic life with long lasting effects.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging fertility. Suspected of damaging the unborn child.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging fertility.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3	Flammable liquids	On basis of test data.
Aquatic Chronic 3	Hazardous to the aquatic environment	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version