

Printing date 23.11.2021

Revision: 23.11.2021

Page 1/9



Printing date 23.11.2021

Revision: 23.11.2021

ide name: Aerosol Kontrollschwarz spezial		
	(Contd. of page 1)	
n-butyl ace		
butan-1-ol		
· Hazard sta	tements	
H222-H22	9 Extremely flammable aerosol. Pressurised container: May burst if heated.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
· Precaution	ary statements	
P101	<i>If medical advice is needed, have product container or label at hand.</i>	
P102	Keep out of reach of children.	
P103	Read carefully and follow all instructions.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P271	Use only outdoors or in a well-ventilated area.	
P305+P35	1+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, ip present and easy to do. Continue rinsing.	
P312	Call a POISON CENTER/doctor if you feel unwell.	
P337+P31	<i>3 If eye irritation persists: Get medical advice/attention.</i>	
P410+P41	2 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.	
· Additional	information:	
Without ad	equate ventilation, explosive atmosphere/gas mix may be created.	
	Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.	
	ontains Hydrocarbons, terpene processing by-products. May produce an allergic reaction.	
· 2.3 Other h	, , , ,, ,, ,	
Results of	PBT and vPvB assessment	
PRT · Not a		

PBT: Not applicable. *vPvB:* Not applicable.

*

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate	50-100%
Reg.nr.: 01-2119475103-46-xxxx CAS: 74-98-6		10-<25%
EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	-
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing $\leq 0,1$ % butadiene (203-450-8)) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane (containing $\leq 0,1$ % butadiene (203-450-8)) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate	5-<10%
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38-xxxx	butan-1-ol ♦ Flam. Liq. 3, H226; < Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-<2.5%
	(Contd. on page

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol Kontrollschwarz spezial

	(Contd. of page 2)
	Hydrocarbons, terpene processing by-products	<i>≥</i> 0.25-<1%
EINECS: 273-309-3	🚸 Flam. Liq. 3, H226; 🚸 Asp. Tox. 1, H304; 🕸 Aquatic	
Reg.nr.: 01-2119980606-28-xxxx	Chronic 2, H411; 🚯 Skin Irrit. 2, H315; Eye Irrit. 2, H319;	
-	Skin Sens. 1, H317	
	•	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

• Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

GB

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol Kontrollschwarz spezial

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.
- **SECTION 8: Exposure controls/personal protection**
- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

141-78-6 ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

106-97-8 butane (containing $\leq 0,1$ % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

71-36-3 butan-1-ol

- WEL Short-term value: 154 mg/m³, 50 ppm Sk
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.
 Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

• **Protection of hands:** Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves Nitrile rubber, NBR

(Contd. on page 5)

⁻ GI

Revision: 23.11.2021

Trade name: Aerosol Kontrollschwarz spezial

(Contd. of page 4)

· Penetration time of glove material

Gloves must be changed after every contamination. The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

 \cdot For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm · *Eye protection:*

Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and c	snemicui properiies	
· General Information		
· Appearance: Form:	Aerosol	
Form: Colour:	According to product specification	
· Odour:	Characteristic	
· Odour. · Odour threshold:	Not determined.	
· pH-value:	Mixture is non-polar/aprotic.	
· Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range	2: -44 °C	
· Flash point:	<0 °C	
· Flammability (solid, gas):	Not applicable.	
· Ignition temperature:	365 °C	
· Decomposition temperature:	Not determined.	
• Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product is not explosive. However, formation of explosive ail vapour mixtures are possible. Not determined.	
· Explosion limits:		
Lower:	1.5 Vol %	
Upper:	11.5 Vol %	
	3,600 hPa	
 Vapour pressure at 20 °C: Relative density 	S,000 nFa Not determined.	
· <i>Vapour density</i>	Not determined.	
• Evaporation rate	Not applicable.	
-	101 uppricuore.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
	(Contd. on page	

Printing date 23.11.2021

Revision: 23.11.2021

		(Contd. of pag
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	96.7 %	
-	With propellant gas. Content given by weight.	
VOC (EU)	96.33 %	
Solids content:	3.7 %	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 53,199 mg/kg (rat)

141-78-6 ethyl acetate

Oral LD50 5,620 mg/kg (rabbit)

Inhalative LC50/4 h 1,600 mg/l (rat)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*

· STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 7)

[·] Primary irritant effect:

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol Kontrollschwarz spezial

(Contd. of page 6)

- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- · 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

- **vPvB:** Ikke relevant.
- · 12.6 Other adverse effects No further relevant information available.
- **SECTION 13: Disposal considerations**
- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
·ADR	
· Class	2 5F Gases.
· Label	2.1
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void not classified
 14.5 Environmental hazards: Marine pollutant: 	No
 14.6 Special precautions for user Hazard identification number (Kemler code): 	Warning: Gases.
	not classified
	(Contd. on page

Printing date 23.11.2021

Revision: 23.11.2021

de name: Aerosol Kontrollschwarz sp	eziai
	(Contd. of page
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
-	SW2 Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre.
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS:
	For wASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
	Segregation as for the appropriate subarvision of class 2.
14.7 Transport in bulk according to A	Annex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities ($\widetilde{E}Q$)	Code: E0
	Not permitted as Excepted Quantity

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

· Technical instructions (air):

Class	Share in %	
NK	50-100	

- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas. H225 Highly flammable liquid and vapour.

(Contd. on page 9)

- GB

Printing date 23.11.2021

Revision: 23.11.2021

rade name: Aerosol Kontrollschwarz spezial	
	(Contd. of page 8)
H226 Flammable liquid and vapour.	
H280 Contains gas under pressure; may explode if heated.	
H302 Harmful if swallowed.	
H304 May be fatal if swallowed and enters airways.	
H315 Causes skin irritation.	
H317 May cause an allergic skin reaction.	
H318 Causes serious eye damage.	
H319 Causes serious eye uninge. H319 Causes serious eye irritation.	
H335 May cause respiratory irritation.	
H336 May cause drowsiness or dizziness.	
H411 Toxic to aquatic life with long lasting effects.	
· Department issuing SDS: Product safety department	
· Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fe	er (Regulations Concerning the
International Transport of Dangerous Goods by Rail)	
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)	
ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)	
ADR: Accord relatif au transport international des marchandises dangereuses par route (Europe	an Agreement Concerning the
International Carriage of Dangerous Goods by Road)	an Agreement concerning the
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Gas 1A: Flammable gases – Category 1A	
Aerosol 1: Aerosols – Category 1	
Press. Gas (Comp.): Gases under pressure – Compressed gas	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Skin Sens. 1: Skin sensitisation – Category 1	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
• * Data compared to the previous version altered.	