


Printing date 08.02.2021

Revision: 08.02.2021



Printing date 08.02.2021

Revision: 08.02.2021

Trade name: Aerosol 1K Universal Fill in fuer Lsm-Lacke 100 ml (Contd. of page 1) · Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read carefully and follow all instructions. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P271 Use only outdoors or in a well-ventilated area. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/attention. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Additional information: Without adequate ventilation, explosive atmosphere/gas mix may be created. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
	dimethyl ether 🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280	50-100%		
	acetone	25-<50%		
	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	1-<2.5%		
Additional information. For they	vording of the listed hazard phrases refer to section 16			

• Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

· After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Generally the product does not irritate the skin.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 08.02.2021

Revision: 08.02.2021

Trade name: Aerosol 1K Universal Fill in fuer Lsm-Lacke 100 ml

(Contd. of page 2)

• **4.3 Indication of any immediate medical attention and special treatment needed** *No further relevant information available.* 

# **SECTION 5: Firefighting measures**

· 5.1 Extinguishing media -

- · Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

## **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles:* Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m<sup>3</sup>, 500 ppm Long-term value: 766 mg/m<sup>3</sup>, 400 ppm

(Contd. on page 4)

Printing date 08.02.2021

Revision: 08.02.2021

Trade name: Aerosol 1K Universal Fill in fuer Lsm-Lacke 100 ml

(Contd. of page 3)

## 67-64-1 acetone

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- · Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

## · Protection of hands:

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- $\cdot$  For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
- butyl rubber, 0,7mm

• Eye protection: Safety glasses



Tightly sealed goggles

# **SECTION 9: Physical and chemical properties**

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:
- Form: Colour: · Odour:

· Odour threshold:

- Aerosol According to product specification Characteristic Not determined. Not determined.
- · pH-value:

(Contd. on page 5)

GB

Printing date 08.02.2021

Revision: 08.02.2021

nde name: Aerosol 1K Universal Fill in fuer Lsm-Lacke 100 ml		
	(Contd. of page	
<ul> <li>Change in condition Melting point/freezing point: Initial boiling point and boiling range</li> </ul>	Undetermined. : -24.9 °C	
· Flash point:	<0 °C Without propellant gas.	
· Flammability (solid, gas):	Not applicable.	
· Ignition temperature:	235 °C	
· Decomposition temperature:	Not determined.	
• Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible. Not determined.	
· Explosion limits: Lower: Upper:	2.6 Vol % 18.6 Vol %	
· Vapour pressure at 20 °C:	3400 hPa	
· Density at 20 °C: · Relative density · Vapour density · Evaporation rate	0.72 g/cm <sup>3</sup> Not determined. Not determined. Not applicable.	
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
· Solvent content: Organic solvents:	100.0 % With propellant gas. Content given by weight.	
VOC (EU)	100.00 %	
Solids content:	0.0 %	
· 9.2 Other information	No further relevant information available.	

# **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)

Printing date 08.02.2021

Revision: 08.02.2021

#### Trade name: Aerosol 1K Universal Fill in fuer Lsm-Lacke 100 ml

(Contd. of page 5)

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- $\cdot$  Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Ikke relevant.
- · 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number		
· ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name		
$\cdot ADR$	1950 AEROSOLS	
·IMDG	AEROSOLS	
· IATA	AEROSOLS, flammable	

Printing date 08.02.2021

Revision: 08.02.2021

	(Contd. of page
14.3 Transport hazard class(es)	
ADR	
2	
$\checkmark$	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
2	
Class	2.1
Label	2.1
14.4 Packing group ADR, IMDG, IATA	Void
	not classified
14.5 Environmental hazards:	, ,
Marine pollutant:	No
-	
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Gases.
manu wennywanon numbel (Remier Coue):	- not classified
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW2 Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre Segregation as for class 9. Stow "separated from" class
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Annex II o	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities $(\widetilde{EQ})$	Code: E0
	Not permitted as Excepted Quantity
Transport category	2 D
Tunnel restriction code	<i>D</i>
	17
Limited quantities (LQ)	1L Code: E0
Excepted quantities (EQ)	<i>Code: E0</i> <i>Not permitted as Excepted Quantity</i>

GB

Printing date 08.02.2021

Revision: 08.02.2021

(Contd. of page 7)

Trade name: Aerosol 1K Universal Fill in fuer Lsm-Lacke 100 ml

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

# **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:

· Technical instructions (air):

Class	Share in %
NK	50-100

• Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Department issuing SDS: Product safety department

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  $\cdot$  \* Data compared to the previous version altered.

GB