

SAFETY DATA SHEET

Metal Protekt Aluminium

According to Regulation (EC) No 1907/2006, Annex II, as amended., COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Metal Protekt Aluminium

Product number 440.0001299.076.05012015

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier

1.4. Emergency telephone number

Emergency telephone +44(0) 844 736 2235
08:00 - 17:00 h (UK)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC/1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336 STOT RE 2 - H373

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram



Signal word

Danger

Metal Protekt Aluminium

Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P271 Use only outdoors or in a well-ventilated area. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/ doctor if you feel unwell. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	Acetone, Ethylbenzene, Solvent Naphtha Light Aromatic (<0.1% Benzene), Stoddard solvent (<0.1% Benzene)
Supplementary precautionary statements	P261 Avoid breathing vapour/ spray. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P314 Get medical advice/ attention if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/ attention.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Acetone	30-60%
CAS number: 67-64-1	EC number: 200-662-2
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
Ethylbenzene	10-30%
CAS number: 100-41-4	EC number: 202-849-4
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 4 - H332	
STOT RE 2 - H373	
Asp. Tox. 1 - H304	

Metal Protekt Aluminium

Propane	10-30%
CAS number: 74-98-6 EC number: 200-827-9	
Classification Flam. Gas 1 - H220 Press. Gas, Liquefied - H280	
Butane	5-10%
CAS number: 106-97-8 EC number: 203-448-7	
Classification Flam. Gas 1 - H220 Press. Gas, Liquefied - H280	
Xylene	5-10%
CAS number: 1330-20-7 EC number: 215-535-7	
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	
Aluminium powder (stabilised)	1-5%
CAS number: 7429-90-5 EC number: 231-072-3	
Classification Flam. Sol. 1 - H228 Water-react. 2 - H261	
Solvent Naphtha Light Aromatic (<0.1% Benzene)	1-5%
CAS number: 64742-95-6 EC number: 265-199-0	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	

Metal Protekt Aluminium

1,2,4-Trimethylbenzene	1-5%
CAS number: 95-63-6	EC number: 202-436-9
Classification	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
STOT SE 3 - H335	
Aquatic Chronic 2 - H411	
Stoddard solvent (<0.1% Benzene)	1-5%
CAS number: 8052-41-3	EC number: 232-489-3
Classification	
Flam. Liq. 3 - H226	
STOT SE 3 - H336	
STOT RE 1 - H372	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	
Cumene	<1%
CAS number: 98-82-8	EC number: 202-704-5
Classification	
Flam. Liq. 3 - H226	
STOT SE 3 - H335	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	
Toluene	< 0.025%
CAS number: 108-88-3	EC number: 203-625-9
Classification	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
Repr. 2 - H361d	
STOT SE 3 - H336	
STOT RE 2 - H373	
Asp. Tox. 1 - H304	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Keep affected person warm and at rest. If in doubt, get medical attention promptly.

Metal Protekt Aluminium

Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.
Ingestion	Due to the physical nature of this product, it is unlikely that ingestion will occur. May cause nausea, headache, dizziness and intoxication.
Skin contact	Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.
Eye contact	Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
Specific treatments	No specific chemical antidote is known to be required after exposure to this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Pressurised container: may burst if heated The product is extremely flammable. In use may form flammable/explosive vapour-air mixture.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Oxides of carbon.

5.3. Advice for firefighters

Protective actions during firefighting	Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Use water spray to reduce vapours.
Special protective equipment for firefighters	Wear chemical protective suit. Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid heat, flames and other sources of ignition. Provide adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Avoid inhalation of vapours/spray and contact with skin and eyes.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Exposure to aquatic environment unlikely. Avoid discharge into drains.
----------------------------------	--

Metal Protekt Aluminium

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Provide adequate ventilation. Absorb spillage with oil-absorbing material.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. During application and drying, solvent vapours will be emitted. Avoid inhalation of vapours and spray/mists. Keep away from heat, sparks and open flame. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Avoid exposing aerosol containers to high temperatures or direct sunlight. Keep away from heat, sparks and open flame. Store in a cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Acetone

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³
Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

Ethylbenzene

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m³
Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m³
Sk

Butane

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³
Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

Xylene

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³
Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³
Sk

Aluminium powder (stabilised)

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust
Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Cumene

Long-term exposure limit (8-hour TWA): WEL 25 ppm 125 mg/m³
Short-term exposure limit (15-minute): WEL 50 ppm 250 mg/m³
Sk

Toluene

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m³
Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m³
Sk

Metal Protekt Aluminium

WEL = Workplace Exposure Limit
Sk = Can be absorbed through the skin.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Personal protective equipment for eye and face protection should comply with European Standard EN166. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

Hand protection

To protect hands from chemicals, gloves should comply with European Standard EN374. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Butyl rubber. Nitrile rubber. Frequent changes are recommended. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Hygiene measures

When using do not eat, drink or smoke. Wash promptly if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove non-impervious clothing that becomes contaminated.

Respiratory protection

This product must not be handled in a confined space without adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Contains low-boiling liquids. Use an air-supplied respirator, if necessary. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible.

Thermal hazards

Contact with liquid form may cause frostbite.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Silver.
Odour	Organic solvents.
pH	Not relevant. The product is insoluble in water.
Melting point	Not available. Technically not feasible.
Initial boiling point and range	-42 °C - 0°C @ 760 mm Hg
Flash point	< -60°C CC (Closed cup).
Evaporation rate	No information available. The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 2 % Upper flammable/explosive limit: 10 %
Vapour pressure	1000 mbar @ 20°C
Vapour density	> 1 Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

Metal Protekt Aluminium

Relative density	~ 0.85
Solubility(ies)	Immiscible with water. Soluble in the following materials: Organic solvents.
Auto-ignition temperature	~450°C
Viscosity	No information available.
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	The product is extremely flammable.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Volatility	Highly volatile.
-------------------	------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not applicable.
---	-----------------

10.4. Conditions to avoid

Conditions to avoid	When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.
----------------------------	--

10.5. Incompatible materials

Materials to avoid	Strong oxidising agents.
---------------------------	--------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	None at ambient temperatures. Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO ₂). Carbon monoxide (CO).
---	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
-------------------------------------	--

Acute toxicity - dermal

Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
---------------------------------------	--

ATE dermal (mg/kg)	13,142.17
---------------------------	-----------

Acute toxicity - inhalation

Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
---	--

ATE inhalation (vapours mg/l)	51.13
--------------------------------------	-------

Skin corrosion/irritation

Metal Protekt Aluminium

Animal data	May cause defatting of the skin but is not an irritant. Repeated exposure may cause skin dryness or cracking.
Extreme pH	Not relevant.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Irritating to eyes. Vapour or spray in the eyes may cause irritation and smarting.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Skin sensitisation	Based on available data the classification criteria are not met.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Central nervous system depression. Vapours may cause drowsiness and dizziness.
Target organs	No specific target organs known.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Target organs	No specific target organs known.
<u>Aspiration hazard</u>	
Aspiration hazard	Not relevant.
<u>Inhalation</u>	
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.
<u>Ingestion</u>	
Ingestion	Due to the physical nature of this product, it is unlikely that ingestion will occur. May cause nausea, headache, dizziness and intoxication.
<u>Skin contact</u>	
Skin contact	Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.
<u>Eye contact</u>	
Eye contact	Irritation of eyes and mucous membranes.
<u>Acute and chronic health hazards</u>	
Acute and chronic health hazards	A single exposure may cause the following adverse effects: Drowsiness.
<u>Route of entry</u>	
Route of entry	Inhalation Dermal Oral
<u>Target organs</u>	
Target organs	No specific target organs known.
<u>Medical symptoms</u>	
Medical symptoms	Fatigue. Headache. Coughing. Dry skin.
<u>Medical considerations</u>	
Medical considerations	Skin disorders and allergies.

Metal Protekt Aluminium

Toxicological information on ingredients.

Acetone

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,800.0

Species Rat

Notes (oral LD₅₀) REACH dossier information.

ATE oral (mg/kg) 5,800.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 15,800.0

Species Rabbit

Notes (dermal LD₅₀) REACH dossier information.

ATE dermal (mg/kg) 15,800.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 132.0

Species Rat

Notes (inhalation LC₅₀) REACH dossier information.

ATE inhalation (vapours mg/l) 132.0

Skin corrosion/irritation

Animal data Dose: 0.01mL, 3 days, Rat
Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Slightly irritating.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising.
Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative.
Based on available data the classification criteria are not met.

Genotoxicity - in vivo Chromosome aberration: Negative.
Based on available data the classification criteria are not met.

Carcinogenicity

Metal Protekt Aluminium

Carcinogenicity	NOEL 79 mg/mouse/application, Dermal, Mouse Based on available data the classification criteria are not met.
Target organ for carcinogenicity	Not relevant.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	One-generation study - NOEL 4858 mg/kg/day, Oral, Mouse P Based on available data the classification criteria are not met.
Reproductive toxicity - development	Maternal toxicity: - NOAEC: 2200 ppm, Inhalation, Rat Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	A single exposure may cause the following adverse effects: Drowsiness, dizziness, disorientation, vertigo.
Target organs	Central nervous system
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
Target organs	Not relevant.
<u>Aspiration hazard</u>	
Aspiration hazard	Not anticipated to present an aspiration hazard, based on chemical structure.

Ethylbenzene

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	3,500.0
Species	Rat
Notes (oral LD₅₀)	REACH dossier information. Based on available data the classification criteria are not met.
ATE oral (mg/kg)	3,500.0
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	15,400.0
Species	Rabbit
Notes (dermal LD₅₀)	REACH dossier information. Based on available data the classification criteria are not met.
ATE dermal (mg/kg)	15,400.0
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	17.2
Species	Rat
Notes (inhalation LC₅₀)	Harmful by inhalation.

Metal Protekt Aluminium

ATE inhalation (vapours mg/l) 17.2

Skin corrosion/irritation

Animal data Dose: 0.01 ml, 24 hours, Rabbit
REACH dossier information. Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Slightly irritating.
Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

Skin sensitisation No information available.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative.
REACH dossier information. Based on available data the classification criteria are not met.

Genotoxicity - in vivo Chromosome aberration: Negative.
REACH dossier information. Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity NOAEL 250 ppm, Inhalation, Rat
REACH dossier information. Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Two-generation study - NOAEC 500 ppm, Inhalation, Rat P
REACH dossier information. Based on available data the classification criteria are not met.

Reproductive toxicity - development Maternal toxicity: - NOAEC: 500 ppm, Inhalation, Rat
REACH dossier information. Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 75 mg/kg, Oral, Rat
REACH dossier information. Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Propane

Acute toxicity - oral

Notes (oral LD₅₀) Technically not feasible.

Metal Protekt Aluminium

Acute toxicity - dermal

Notes (dermal LD₅₀) Technically not feasible.

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ gases ppmV) 800,000.0

Species Rat

Notes (inhalation LC₅₀) REACH dossier information.

ATE inhalation (gases ppm) 800,000.0

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative. Based on available data the classification criteria are not met.

Genotoxicity - in vivo Chromosome aberration: Negative. Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Screening - NOAEC 9000 ppm, Inhalation, Rat P Based on available data the classification criteria are not met.

Reproductive toxicity - development Maternal toxicity: - NOAEC: 12000 ppm, Inhalation, Rat Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

Butane

Acute toxicity - oral

Notes (oral LD₅₀) Technically not feasible.

Metal Protekt Aluminium

Acute toxicity - dermal

Notes (dermal LD₅₀) Technically not feasible.

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ gases ppmV) 539,600.0

Species Mouse

Notes (inhalation LC₅₀) REACH dossier information. Based on available data the classification criteria are not met.

ATE inhalation (gases ppm) 539,600.0

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Technically not feasible.

Germ cell mutagenicity

Genotoxicity - in vitro Bacterial reverse mutation test: Negative. Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Not determined. Scientifically unjustified.

Reproductive toxicity

Reproductive toxicity - fertility Fertility - NOAEC 9000 ppm, Inhalation, Rat P REACH dossier information. Based on available data the classification criteria are not met.

Reproductive toxicity - development Maternal toxicity: - NOAEC: 12000 ppm, Inhalation, Rat REACH dossier information. Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEC 9000 ppm, Inhalation, Rat REACH dossier information. Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

Xylene

Acute toxicity - oral

Metal Protekt Aluminium

Acute toxicity oral (LD₅₀ mg/kg)	3,523.0
Species	Rat
Notes (oral LD₅₀)	REACH dossier information. Based on available data the classification criteria are not met.
ATE oral (mg/kg)	3,523.0
<u>Acute toxicity - dermal</u>	
Notes (dermal LD₅₀)	Harmful in contact with skin.
ATE dermal (mg/kg)	1,100.0
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ gases ppmV)	6,700.0
Species	Rat
Acute toxicity inhalation (LC₅₀ vapours mg/l)	29.0
Species	Rat
Notes (inhalation LC₅₀)	Harmful by inhalation.
ATE inhalation (vapours mg/l)	11.0
<u>Skin corrosion/irritation</u>	
Animal data	Rabbit Primary dermal irritation index: 2.21 REACH dossier information. Moderately irritating.
Extreme pH	Moderate pH (> 2 and < 11.5).
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Based on available data the classification criteria are not met.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	No information available.
<u>Skin sensitisation</u>	
Skin sensitisation	Local Lymph Node Assay (LLNA) - Mouse: Not sensitising. REACH dossier information. Based on available data the classification criteria are not met.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Chromosome aberration: Negative. REACH dossier information. Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Chromosome aberration: Negative. REACH dossier information. Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	

Metal Protekt Aluminium

Carcinogenicity	NOAEL 1000 mg/kg/day, Oral, Rat REACH dossier information. No evidence of carcinogenicity in animal studies.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Two-generation study - NOAEC 500 ppm, Inhalation, Rat P REACH dossier information. Based on available data the classification criteria are not met.
Reproductive toxicity - development	Developmental toxicity: - NOAEC: 500 ppm, Inhalation, REACH dossier information. Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	NOAEC 500 ppm, Inhalation, Rat REACH dossier information. Not classified as a specific target organ toxicant after repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity	The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
-----------------	--

Ecological information on ingredients.

Acetone

Toxicity	Not considered toxic to fish.
Acute toxicity - fish	LC ₅₀ , 96 hours: 5540 mg/l, Onchorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 12700 mg/l, Daphnia magna
Acute toxicity - aquatic plants	NOEC, 192 hours: 530 mg/l, Microcystis aeruginosa
Chronic toxicity - aquatic invertebrates	NOEC, 28 days: 2212 mg/l, Daphnia magna

Ethylbenzene

Acute toxicity - fish	LC ₅₀ , 96 hours: 4.2 mg/l, Onchorhynchus mykiss (Rainbow trout) REACH dossier information.
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 2.1 mg/l, Daphnia magna REACH dossier information.
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 5.4 mg/l, Selenastrum capricornutum REACH dossier information.

Propane

Metal Protekt Aluminium

Acute toxicity - fish	LC ₅₀ , 96 hours: 27.98 mg/l, Estimated value.
Acute toxicity - aquatic invertebrates	LC ₅₀ , 48 hours: 14.22 mg/l, Estimated value.
Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: 7.71 mg/l, Estimated value.
Chronic toxicity - fish early life stage	No information available.

Butane

Acute toxicity - fish	LC ₅₀ , 96 hours: 24.1 mg/l, Estimated value.
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 14.2 mg/l, Estimated value.
Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: 7.7 mg/l, Estimated value.

Xylene

Acute toxicity - fish	LC ₅₀ , 96 hours: 2.6 mg/l, Onchorhynchus mykiss (Rainbow trout) REACH dossier information.
Acute toxicity - aquatic invertebrates	NOEC, 48 hours: 3.4 mg/l, Daphnia magna REACH dossier information.
Acute toxicity - aquatic plants	EC ₅₀ , 73 hours: 4.36 mg/l, Selenastrum capricornutum REACH dossier information.

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known. The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. Volatile substances are degraded in the atmosphere within a few days.

Ecological information on ingredients.

Acetone

Persistence and degradability	The substance is readily biodegradable.
Phototransformation	Water - DT ₅₀ : 20-115 days
Stability (hydrolysis)	No significant reaction in water.
Biodegradation	Water - Degradation 90: 28 days

Ethylbenzene

Phototransformation	Water - Degradation 50: 2.3 days REACH dossier information.
Stability (hydrolysis)	No significant reaction in water.

Metal Protekt Aluminium

Biodegradation Water - Degradation 79: 28 days
REACH dossier information.
The substance is readily biodegradable.

Propane

Persistence and degradability Highly volatile.

Phototransformation Water - DT₅₀ : 1906 days

Stability (hydrolysis) Not applicable.

Biodegradation Water - 100%: 385.5 hours

Butane

Phototransformation Not determined.

Stability (hydrolysis) No significant reaction in water.

Biodegradation Water - DT₅₀ : 3.5 days
Estimated value.
The substance is readily biodegradable.

Xylene

Phototransformation Water - DT₅₀ : 1.09 days
Estimated value.
REACH dossier information.

Stability (hydrolysis) No significant reaction in water.

Biodegradation Water - Degradation 87.8: 28 days
REACH dossier information.
The substance is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

Ecological information on ingredients.

Acetone

Bioaccumulative potential BCF: 3,
Estimated value.

Partition coefficient log Pow: -0.24

Ethylbenzene

Bioaccumulative potential BCF: 1, Onchorhynchus mykiss (Rainbow trout)
REACH dossier information. The product is not bioaccumulating.

Partition coefficient log Pow: 3.6 REACH dossier information.

Propane

Partition coefficient log Pow: 1.09

Metal Protekt Aluminium

Butane

Bioaccumulative potential The product is not bioaccumulating.

Xylene

Bioaccumulative potential BCF: < 25.9,
The product is not bioaccumulating. REACH dossier information.

Partition coefficient log Pow: ~ 3.1
REACH dossier information.

12.4. Mobility in soil

Mobility The product is immiscible with water and will spread on the water surface. The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Ecological information on ingredients.

Acetone

Mobility Highly volatile. Soluble in water.

Henry's law constant 2.303 Pa m³/mol @ 15°C

Ethylbenzene

Mobility Volatile liquid. The product is immiscible with water and will spread on the water surface.

Henry's law constant 0.0083 atm m³/mol @ 25°C
REACH dossier information.

Surface tension 71.2 mN/m @ 23°C
REACH dossier information.

Propane

Mobility Highly volatile.

Butane

Mobility The product is insoluble in water. Highly volatile.

Xylene

Mobility The product is insoluble in water and will spread on the water surface.

Adsorption/desorption coefficient Water - log Koc: ~ 2.7 @ 25°C
REACH dossier information.

Henry's law constant ~ 623 Pa m³/mol @ 25°C
REACH dossier information.

Surface tension ~ 29 mN/m @ 25°C
REACH dossier information.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Metal Protekt Aluminium

Ecological information on ingredients.

Acetone

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

Ethylbenzene

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

Propane

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

Butane

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

Xylene

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.

Acetone

Other adverse effects None known.

Ethylbenzene

Other adverse effects None known.

Propane

Other adverse effects None known.

Butane

Other adverse effects None known.

Xylene

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Metal Protekt Aluminium

General information	Information given is applicable to the product as supplied. When handling waste, the safety precautions applying to handling of the product should be considered. Do not puncture or incinerate, even when empty. Reuse or recycle products wherever possible.
Disposal methods	Do not empty into drains. Dispose of waste product or used containers in accordance with local regulations Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste and repealing certain Directives.
Waste class	Information given is applicable to the product as supplied. [08 01 11*] / [20 01 27*]

SECTION 14: Transport information

General For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	Aerosols, flammable
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2 (5F)
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Metal Protekt Aluminium

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-D, S-U

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824). EH40/2005 Workplace exposure limits.
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste and repealing certain Directives.
Health and environmental listings	Regulation (EC) No 2037/2000 of the European Parliament and of the Council of 29 June 2000 on substances that deplete the ozone layer (as amended). Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants (as amended). Regulation (EC) 689/2008 of the European Parliament and of the Council of 17 June 2008 concerning the export and import of dangerous chemicals (as amended). None of the ingredients are listed.
Authorisations (Title VII Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Title VIII Regulation 1907/2006)	No specific restrictions on use are known for this product.
SEVESO	P3a - Lower tier 150 tonnes, Upper tier 500 tonnes.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Metal Protekt Aluminium

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 IMDG: International Maritime Dangerous Goods.
 IATA: International Air Transport Association.
 ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air.
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
 ATE: Acute Toxicity Estimate.
 LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
 LC₅₀: Lethal Concentration to 50 % of a test population.
 LOAEC: Lowest Observed Adverse Effect Concentration.
 NOAEC: No Observed Adverse Effect Concentration.
 EC₅₀: 50% of maximal Effective Concentration.
 PBT: Persistent, Bioaccumulative and Toxic substance.
 vPvB: Very Persistent and Very Bioaccumulative.
 BCF: Bioconcentration Factor.
 Kow: Octanol-water partition coefficient.

Classification abbreviations and acronyms

Aerosol = Aerosol
 Eye Irrit. = Eye irritation
 STOT SE = Specific target organ toxicity-single exposure
 STOT RE = Specific target organ toxicity-repeated exposure
 Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Classification procedures according to Regulation (EC) 1272/2008

Aerosol 1 - H222, H229: Bridging principle (Aerosols). Eye Irrit. 2 - H319, STOT SE 3 - H336, STOT RE 2 - H373, Aquatic Chronic 3 - H412: Calculation method. EUH066: Expert judgement.

Revision date

01/03/2016

Revision

3

Supersedes date

05/01/2015

SDS number

757

Metal Protekt Aluminium

Hazard statements in full

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H226 Flammable liquid and vapour.
H228 Flammable solid.
H229 Pressurised container: may burst if heated
H229 Pressurised container: may burst if heated
H261 In contact with water releases flammable gases.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs (Hearing organs) through prolonged or repeated exposure.
H373 May cause damage to organs (Hearing organs) through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.